



IEC 61169-47

Edition 2.0 2015-03

INTERNATIONAL STANDARD



**Radio-frequency connectors –
Part 47: Sectional specification for radio-frequency coaxial connectors with
clamp coupling, typically for use in 75 Ω cable networks (type F-Quick)**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.120.30

ISBN 978-2-8322-2581-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references.....	6
3 Interface dimensions.....	6
3.1 Dimensions.....	6
3.1.1 Common dimensions.....	6
3.1.2 Example of connector “F-Quick” type male plug with resilient outer conductor sleeve (indoor) physical dimensions.....	7
3.1.3 Example of connector “F-Quick” type male plug with slotted outer conductor (indoor) physical dimensions.....	8
3.1.4 Example of connector “F-Quick” type male plug with slotted outer conductor and snap ring (indoor) physical dimensions.....	8
3.2 Mechanical gauges.....	9
4 Quality assessment procedures.....	10
4.1 General.....	10
4.2 Ratings and characteristics.....	10
4.3 Environmental characteristics for outdoor sockets.....	12
4.4 Test schedule and inspection requirements.....	12
4.4.1 Acceptance tests.....	12
4.4.2 Periodic tests.....	12
4.5 Procedures for the quality conformance.....	14
4.5.1 Quality conformance inspection.....	14
4.5.2 Quality conformance and its maintenance – General procedure.....	14
5 Instructions for preparation of detail specifications.....	14
5.1 General.....	14
5.2 Identification of the component.....	14
5.3 Performance.....	15
5.4 Marking, ordering information and related matters.....	15
5.5 Selection of tests, test conditions and severities.....	15
5.6 Blank detail specification pro-forma for type F-QUICK connector.....	16
6 Marking.....	20
6.1 Marking of component.....	20
6.2 Marking and contents of package.....	20
Figure 1 – Connector “F-Quick” type male plug: general dimensions.....	7
Figure 2 – Example of connector “F-Quick” type male plug with resilient outer conductor sleeve (indoor).....	8
Figure 3 – Example of connector “F-Quick” type male plug with slotted outer conductor (indoor).....	8
Figure 4 – Example of connector “F-Quick” type male plug with slotted outer conductor and snap ring (indoor).....	9
Figure 5 – Mechanical gauge for resilient outer conductor.....	9

Table 1 – Connector “F” type male plug (indoor)7

Table 2 – Ratings and characteristics 10

Table 3 – Acceptance tests 12

Table 4 – Periodic tests 13

INTERNATIONAL ELECTROTECHNICAL COMMISSION

RADIO-FREQUENCY CONNECTORS –**Part 47: Sectional specification for radio-frequency coaxial
connectors with clamp coupling, typically for use in
75 Ω cable networks (type F-Quick)**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61169-47 has been prepared by subcommittee 46F: R.F. and microwave passive components, of IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

This second edition cancels and replaces the first edition published in 2012. It constitutes a technical revision.

The main changes are listed below:

- Subclause 3.2 has been updated to better define gauging.
- Table 2 has been updated for insertion and removal forces.
- Clause 4 has been updated to refer to the new edition of IEC 61169-1.

The text of this standard is based on the following documents:

CDV	Report on voting
46F/272/CDV	46F/306/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61169 series, under the general title: *Radio-frequency connectors*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

RADIO-FREQUENCY CONNECTORS –

Part 47: Sectional specification for radio-frequency coaxial connectors with clamp coupling, typically for use in 75 Ω cable networks (type F-Quick)

1 Scope

This part of IEC 61169, which is a sectional specification (SS), provides information and rules for the preparation of detail specifications (DS) for RF coaxial connectors with clamp coupling, typically for use in 75 Ω cable networks (type F-Quick).

It describes the interface dimensions with gauging information, electrical and mechanical performance including the mandatory tests selected from IEC 61169-1:2013, applicable to all DS relating to type F-Quick connectors.

This specification indicates the recommended performance characteristics to be considered when writing a DS and covers test schedules and inspection requirements.

NOTE This interface is typically used for indoor connections, which are easily disconnected and reconnected. The typical application is for F-type coaxial receiver leads or F-type coaxial patch cables. The interface may also be known as a Push-on connector. It is preferred to use the fixed (screwed) connectors type F according to IEC 61169-24:2009.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61169-1:2013, *Radio-frequency connectors – Part 1: Generic specification – General requirements and measuring methods*

IEC 61169-24:2009, *Radio-frequency connectors – Part 24: Sectional specification – Radio frequency coaxial connectors with screw coupling, typically for use in 75 Ω cable networks (type F)*

IEC 62037 (all parts), *Passive RF and microwave devices, intermodulation level measurement*

IEC 62037-3, *Passive RF and microwave devices, intermodulation level measurement – Part 3: Measurement of passive intermodulation in coaxial connectors*