



IEC 62680-2-1

Edition 1.0 2015-09

# INTERNATIONAL STANDARD



---

**Universal serial bus interfaces for data and power –  
Part 2-1: Universal Serial Bus Specification, Revision 2.0**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

ICS 29.220; 33.120; 35.200

ISBN 978-2-8322-2845-6

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

### UNIVERSAL SERIAL BUS INTERFACES FOR DATA AND POWER –

#### Part 2-1: Universal Serial Bus Specification, Revision 2.0

#### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62680-2-1 has been prepared by technical area 14: Interfaces and methods of measurement for personal computing equipment, of IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard is based on documents prepared by the USB Implementers Forum (USB-IF). The structure and editorial rules used in this publication reflect the practice of the organization which submitted it.

This first edition cancels and replaces IEC 62680-1 published in 2013. This edition constitutes a technical revision.

This bilingual version (2018-10) corresponds to the English version, published in 2015-09.

The text of this standard is based on the following documents:

| CDV          | Report on voting |
|--------------|------------------|
| 100/2331/CDV | 100/2434/RVC     |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The French version of this standard has not been voted upon.

A list of all the parts in the IEC 62680 series, published under the general title *Universal serial bus interfaces for data and power* can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## INTRODUCTION

The IEC 62680 series is based on a series of specifications that were originally developed by the USB Implementers Forum (USB-IF). These specifications were submitted to the IEC under the auspices of a special agreement between the IEC and the USB IF.

The USB Implementers Forum, Inc.(USB-IF) is a non-profit corporation founded by the group of companies that developed the Universal Serial Bus specification. The USB-IF was formed to provide a support organization and forum for the advancement and adoption of Universal Serial Bus technology. The Forum facilitates the development of high-quality compatible USB peripherals (devices), and promotes the benefits of USB and the quality of products that have passed compliance testing.

**ANY USB SPECIFICATIONS ARE PROVIDED TO YOU "AS IS, "WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE USB IMPLEMENTERS FORUM AND THE AUTHORS OF ANY USB SPECIFICATIONS DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OR INFORMATION IN THIS SPECIFICATION.**

**THE PROVISION OF ANY USB SPECIFICATIONS TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS.**

Entering into USB Adopters Agreements may, however, allow a signing company to participate in a reciprocal, royalty-free licensing arrangement for compliant products. For more information, please see:

<http://www.usb.org/developers/docs/>  
[http://www.usb.org/developers/devclass\\_docs#approved](http://www.usb.org/developers/devclass_docs#approved)

IEC DOES NOT TAKE ANY POSITION AS TO WHETHER IT IS ADVISABLE FOR YOU TO ENTER INTO ANY USB ADOPTERS AGREEMENTS OR TO PARTICIPATE IN THE USB IMPLEMENTERS FORUM."

*This series covers the Universal Serial Bus interfaces for data and power and consists of the following parts:*

IEC 62680-1-1, *Universal Serial Bus interfaces for data and power – Part 1-1: Common components – USB Battery Charging Specification, Revision 1.2*

IEC 62680-2-1, *Universal Serial Bus interfaces for data and power – Part 2-1: Universal Serial Bus Specification, Revision 2.0*

IEC 62680-2-2, *Universal Serial Bus interfaces for data and power – Part 2-2: USB Micro-USB Cables and Connectors Specification, Revision 1.01*

IEC 62680-2-3, *Universal Serial Bus interfaces for data and power – Part 2-3: Universal Serial Bus Cables and Connectors Class Document, Revision 2.0*

This part of the IEC 62680 series consists of several distinct parts:

- the main body of the text, which consists of the original specification and all ECN and Errata developed by the USB-IF.

## CONTENTS

|                                              |    |
|----------------------------------------------|----|
| FOREWORD .....                               | 2  |
| INTRODUCTION .....                           | 4  |
| 1 Chapter 1 Introduction .....               | 29 |
| 1.1 Motivation .....                         | 29 |
| 1.2 Objective of the Specification .....     | 29 |
| 1.3 Scope of the Document .....              | 30 |
| 1.4 USB Product Compliance .....             | 30 |
| 1.5 Document Organization .....              | 30 |
| 2 Chapter 2 Terms and Abbreviations .....    | 31 |
| 3 Chapter 3 Background .....                 | 37 |
| 3.1 Goals for the Universal Serial Bus ..... | 37 |
| 3.2 Taxonomy of Application Space .....      | 37 |
| 3.3 Feature List .....                       | 38 |
| 4 Chapter 4 Architectural Overview .....     | 40 |
| 4.1 USB System Description .....             | 40 |
| 4.1.1 Bus Topology .....                     | 40 |
| 4.2 Physical Interface .....                 | 41 |
| 4.2.1 Electrical .....                       | 42 |
| 4.2.2 Mechanical .....                       | 42 |
| 4.3 Power .....                              | 42 |
| 4.3.1 Power Distribution .....               | 43 |
| 4.3.2 Power Management .....                 | 43 |
| 4.4 Bus Protocol .....                       | 43 |
| 4.5 Robustness .....                         | 43 |
| 4.5.1 Error Detection .....                  | 44 |
| 4.5.2 Error Handling .....                   | 44 |
| 4.6 System Configuration .....               | 44 |
| 4.6.1 Attachment of USB Devices .....        | 44 |
| 4.6.2 Removal of USB Devices .....           | 44 |
| 4.6.3 Bus Enumeration .....                  | 45 |
| 4.7 Data Flow Types .....                    | 45 |
| 4.7.1 Control Transfers .....                | 45 |
| 4.7.2 Bulk Transfers .....                   | 45 |
| 4.7.3 Interrupt Transfers .....              | 45 |
| 4.7.4 Isochronous Transfers .....            | 46 |
| 4.7.5 Allocating USB Bandwidth .....         | 46 |
| 4.8 USB Devices .....                        | 46 |
| 4.8.1 Device Characterizations .....         | 46 |
| 4.8.2 Device Descriptions .....              | 47 |
| 4.9 USB Host: Hardware and Software .....    | 49 |
| 4.10 Architectural Extensions .....          | 49 |
| 5 Chapter 5 USB Data Flow Model .....        | 50 |
| 5.1 Implementer Viewpoints .....             | 50 |
| 5.2 Bus Topology .....                       | 51 |
| 5.2.1 USB Host .....                         | 52 |
| 5.2.2 USB Devices .....                      | 52 |

|        |                                                          |    |
|--------|----------------------------------------------------------|----|
| 5.2.3  | Physical Bus Topology .....                              | 53 |
| 5.2.4  | Logical Bus Topology .....                               | 54 |
| 5.2.5  | Client Software-to-function Relationship .....           | 55 |
| 5.3    | USB Communication Flow.....                              | 55 |
| 5.3.1  | Device Endpoints.....                                    | 57 |
| 5.3.2  | Pipes .....                                              | 58 |
| 5.3.3  | Frames and Microframes .....                             | 60 |
| 5.4    | Transfer Types.....                                      | 60 |
| 5.4.1  | Table Calculation Examples.....                          | 61 |
| 5.5    | Control Transfers .....                                  | 62 |
| 5.5.1  | Control Transfer Data Format .....                       | 62 |
| 5.5.2  | Control Transfer Direction.....                          | 63 |
| 5.5.3  | Control Transfer Packet Size Constraints .....           | 63 |
| 5.5.4  | Control Transfer Bus Access Constraints.....             | 64 |
| 5.5.5  | Control Transfer Data Sequences .....                    | 66 |
| 5.6    | Isochronous Transfers .....                              | 67 |
| 5.6.1  | Isochronous Transfer Data Format.....                    | 67 |
| 5.6.2  | Isochronous Transfer Direction .....                     | 67 |
| 5.6.3  | Isochronous Transfer Packet Size Constraints .....       | 67 |
| 5.6.4  | Isochronous Transfer Bus Access Constraints .....        | 69 |
| 5.6.5  | Isochronous Transfer Data Sequences .....                | 70 |
| 5.7    | Interrupt Transfers .....                                | 70 |
| 5.7.1  | Interrupt Transfer Data Format .....                     | 70 |
| 5.7.2  | Interrupt Transfer Direction.....                        | 70 |
| 5.7.3  | Interrupt Transfer Packet Size Constraints.....          | 70 |
| 5.7.4  | Interrupt Transfer Bus Access Constraints.....           | 71 |
| 5.7.5  | Interrupt Transfer Data Sequences .....                  | 74 |
| 5.8    | Bulk Transfers .....                                     | 74 |
| 5.8.1  | Bulk Transfer Data Format.....                           | 74 |
| 5.8.2  | Bulk Transfer Direction .....                            | 74 |
| 5.8.3  | Bulk Transfer Packet Size Constraints .....              | 74 |
| 5.8.4  | Bulk Transfer Bus Access Constraints .....               | 75 |
| 5.8.5  | Bulk Transfer Data Sequences .....                       | 76 |
| 5.9    | High-Speed, High Bandwidth Endpoints .....               | 77 |
| 5.9.1  | High Bandwidth Interrupt Endpoints.....                  | 77 |
| 5.9.2  | High Bandwidth Isochronous Endpoints .....               | 78 |
| 5.10   | Split Transactions .....                                 | 79 |
| 5.11   | Bus Access for Transfers .....                           | 79 |
| 5.11.1 | Transfer Management.....                                 | 80 |
| 5.11.2 | Transaction Tracking .....                               | 82 |
| 5.11.3 | Calculating Bus Transaction Times .....                  | 84 |
| 5.11.4 | Calculating Buffer Sizes in Functions and Software ..... | 86 |
| 5.11.5 | Bus Bandwidth Reclamation .....                          | 86 |
| 5.12   | Special Considerations for Isochronous Transfers.....    | 86 |
| 5.12.1 | Example Non-USB Isochronous Application.....             | 88 |
| 5.12.2 | USB Clock Model.....                                     | 89 |
| 5.12.3 | Clock Synchronization .....                              | 91 |
| 5.12.4 | Isochronous Devices .....                                | 91 |
| 5.12.5 | Data Prebuffering .....                                  | 99 |

|        |                                                                      |     |
|--------|----------------------------------------------------------------------|-----|
| 5.12.6 | SOF Tracking .....                                                   | 100 |
| 5.12.7 | Error Handling .....                                                 | 100 |
| 5.12.8 | Buffering for Rate Matching .....                                    | 101 |
| 6      | Chapter 6 Mechanical .....                                           | 103 |
| 6.1    | Architectural Overview .....                                         | 103 |
| 6.2    | Keyed Connector Protocol .....                                       | 103 |
| 6.3    | Cable .....                                                          | 104 |
| 6.4    | Cable Assembly .....                                                 | 104 |
| 6.4.1  | Standard Detachable Cable Assemblies .....                           | 104 |
| 6.4.2  | High-/full-speed Captive Cable Assemblies .....                      | 106 |
| 6.4.3  | Low-speed Captive Cable Assemblies .....                             | 108 |
| 6.4.4  | Prohibited Cable Assemblies .....                                    | 110 |
| 6.5    | Connector Mechanical Configuration and Material Requirements .....   | 110 |
| 6.5.1  | USB Icon Location .....                                              | 111 |
| 6.5.2  | USB Connector Termination Data .....                                 | 111 |
| 6.5.3  | Series “A” and Series “B” Receptacles .....                          | 112 |
| 6.5.4  | Series “A” and Series “B” Plugs .....                                | 115 |
| 6.6    | Cable Mechanical Configuration and Material Requirements .....       | 118 |
| 6.6.1  | Description .....                                                    | 119 |
| 6.6.2  | Construction .....                                                   | 119 |
| 6.6.3  | Electrical Characteristics .....                                     | 122 |
| 6.6.4  | Cable Environmental Characteristics .....                            | 122 |
| 6.6.5  | Listing .....                                                        | 122 |
| 6.7    | Electrical, Mechanical, and Environmental Compliance Standards ..... | 123 |
| 6.7.1  | Applicable Documents .....                                           | 128 |
| 6.8    | USB Grounding .....                                                  | 128 |
| 6.9    | PCB Reference Drawings .....                                         | 128 |
| 7      | Chapter 7 Electrical .....                                           | 132 |
| 7.1    | Signaling .....                                                      | 132 |
| 7.1.1  | USB Driver Characteristics .....                                     | 135 |
| 7.1.2  | Data Signal Rise and Fall, Eye Patterns .....                        | 142 |
| 7.1.3  | Cable Skew .....                                                     | 151 |
| 7.1.4  | Receiver Characteristics .....                                       | 151 |
| 7.1.5  | Device Speed Identification .....                                    | 153 |
| 7.1.6  | Input Characteristics .....                                          | 154 |
| 7.1.7  | Signaling Levels .....                                               | 157 |
| 7.1.8  | Data Encoding/Decoding .....                                         | 170 |
| 7.1.9  | Bit Stuffing .....                                                   | 170 |
| 7.1.10 | Sync Pattern .....                                                   | 172 |
| 7.1.11 | Data Signaling Rate .....                                            | 173 |
| 7.1.12 | Frame Interval .....                                                 | 173 |
| 7.1.13 | Data Source Signaling .....                                          | 174 |
| 7.1.14 | Hub Signaling Timings .....                                          | 175 |
| 7.1.15 | Receiver Data Jitter .....                                           | 177 |
| 7.1.16 | Cable Delay .....                                                    | 179 |
| 7.1.17 | Cable Attenuation .....                                              | 180 |
| 7.1.18 | Bus Turn-around Time and Inter-packet Delay .....                    | 181 |
| 7.1.19 | Maximum End-to-end Signal Delay .....                                | 182 |
| 7.1.20 | Test Mode Support .....                                              | 183 |

|       |                                               |     |
|-------|-----------------------------------------------|-----|
| 7.2   | Power Distribution.....                       | 184 |
| 7.2.1 | Classes of Devices .....                      | 184 |
| 7.2.2 | Voltage Drop Budget .....                     | 189 |
| 7.2.3 | Power Control During Suspend/Resume .....     | 189 |
| 7.2.4 | Dynamic Attach and Detach.....                | 190 |
| 7.3   | Physical Layer .....                          | 191 |
| 7.3.1 | Regulatory Requirements .....                 | 191 |
| 7.3.2 | Bus Timing/Electrical Characteristics .....   | 192 |
| 7.3.3 | Timing Waveforms .....                        | 202 |
| 8     | Chapter 8 Protocol Layer.....                 | 205 |
| 8.1   | Byte/Bit Ordering .....                       | 205 |
| 8.2   | SYNC Field.....                               | 205 |
| 8.3   | Packet Field Formats .....                    | 205 |
| 8.3.1 | Packet Identifier Field .....                 | 205 |
| 8.3.2 | Address Fields.....                           | 206 |
| 8.3.3 | Frame Number Field .....                      | 207 |
| 8.3.4 | Data Field.....                               | 207 |
| 8.3.5 | Cyclic Redundancy Checks.....                 | 208 |
| 8.4   | Packet Formats.....                           | 209 |
| 8.4.1 | Token Packets.....                            | 209 |
| 8.4.2 | Split Transaction Special Token Packets ..... | 209 |
| 8.4.3 | Start-of-Frame Packets.....                   | 214 |
| 8.4.4 | Data Packets.....                             | 215 |
| 8.4.5 | Handshake Packets .....                       | 216 |
| 8.4.6 | Handshake Responses .....                     | 217 |
| 8.5   | Transaction Packet Sequences .....            | 218 |
| 8.5.1 | NAK Limiting via Ping Flow Control.....       | 227 |
| 8.5.2 | Bulk Transactions .....                       | 231 |
| 8.5.3 | Control Transfers.....                        | 236 |
| 8.5.4 | Interrupt Transactions.....                   | 239 |
| 8.5.5 | Isochronous Transactions .....                | 239 |
| 8.6   | Data Toggle Synchronization and Retry .....   | 243 |
| 8.6.1 | Initialization via SETUP Token.....           | 244 |
| 8.6.2 | Successful Data Transactions.....             | 244 |
| 8.6.3 | Data Corrupted or Not Accepted .....          | 245 |
| 8.6.4 | Corrupted ACK Handshake .....                 | 245 |
| 8.6.5 | Low-speed Transactions .....                  | 246 |
| 8.7   | Error Detection and Recovery .....            | 247 |
| 8.7.1 | Packet Error Categories .....                 | 247 |
| 8.7.2 | Bus Turn-around Timing .....                  | 247 |
| 8.7.3 | False EOPs .....                              | 248 |
| 8.7.4 | Babble and Loss of Activity Recovery .....    | 249 |
| 9     | Chapter 9 USB Device Framework.....           | 250 |
| 9.1   | USB Device States .....                       | 250 |
| 9.1.1 | Visible Device States .....                   | 250 |
| 9.1.2 | Bus Enumeration .....                         | 254 |
| 9.2   | Generic USB Device Operations .....           | 254 |
| 9.2.1 | Dynamic Attachment and Removal .....          | 255 |
| 9.2.2 | Address Assignment.....                       | 255 |



|        |                                                  |     |
|--------|--------------------------------------------------|-----|
| 9.2.3  | Configuration .....                              | 255 |
| 9.2.4  | Data Transfer .....                              | 256 |
| 9.2.5  | Power Management .....                           | 256 |
| 9.2.6  | Request Processing .....                         | 256 |
| 9.2.7  | Request Error .....                              | 258 |
| 9.3    | USB Device Requests .....                        | 259 |
| 9.3.1  | bmRequestType .....                              | 259 |
| 9.3.2  | bRequest .....                                   | 259 |
| 9.3.3  | wValue .....                                     | 259 |
| 9.3.4  | wIndex .....                                     | 260 |
| 9.3.5  | wLength .....                                    | 260 |
| 9.4    | Standard Device Requests .....                   | 260 |
| 9.4.1  | Clear Feature .....                              | 262 |
| 9.4.2  | Get Configuration .....                          | 263 |
| 9.4.3  | Get Descriptor .....                             | 263 |
| 9.4.4  | Get Interface .....                              | 264 |
| 9.4.5  | Get Status .....                                 | 264 |
| 9.4.6  | Set Address .....                                | 266 |
| 9.4.7  | Set Configuration .....                          | 266 |
| 9.4.8  | Set Descriptor .....                             | 267 |
| 9.4.9  | Set Feature .....                                | 268 |
| 9.4.10 | Set Interface .....                              | 269 |
| 9.4.11 | Synch Frame .....                                | 269 |
| 9.5    | Descriptors .....                                | 270 |
| 9.6    | Standard USB Descriptor Definitions .....        | 270 |
| 9.6.1  | Device .....                                     | 270 |
| 9.6.2  | Device_Qualifier .....                           | 272 |
| 9.6.3  | Configuration .....                              | 273 |
| 9.6.4  | Other_Speed_Configuration .....                  | 275 |
| 9.6.5  | Interface .....                                  | 275 |
| 9.6.6  | Endpoint .....                                   | 276 |
| 9.6.7  | String .....                                     | 279 |
| 9.7    | Device Class Definitions .....                   | 280 |
| 9.7.1  | Descriptors .....                                | 280 |
| 9.7.2  | Interface(s) and Endpoint Usage .....            | 280 |
| 9.7.3  | Requests .....                                   | 281 |
| 10     | Chapter 10 USB Host: Hardware and Software ..... | 282 |
| 10.1   | Overview of the USB Host .....                   | 282 |
| 10.1.1 | Overview .....                                   | 282 |
| 10.1.2 | Control Mechanisms .....                         | 285 |
| 10.1.3 | Data Flow .....                                  | 285 |
| 10.1.4 | Collecting Status and Activity Statistics .....  | 286 |
| 10.1.5 | Electrical Interface Considerations .....        | 286 |
| 10.2   | Host Controller Requirements .....               | 286 |
| 10.2.1 | State Handling .....                             | 287 |
| 10.2.2 | Serializer/Deserializer .....                    | 287 |
| 10.2.3 | Frame and Microframe Generation .....            | 287 |
| 10.2.4 | Data Processing .....                            | 288 |
| 10.2.5 | Protocol Engine .....                            | 288 |

|        |                                                            |     |
|--------|------------------------------------------------------------|-----|
| 10.2.6 | Transmission Error Handling.....                           | 288 |
| 10.2.7 | Remote Wakeup .....                                        | 289 |
| 10.2.8 | Root Hub .....                                             | 289 |
| 10.2.9 | Host System Interface .....                                | 289 |
| 10.3   | Overview of Software Mechanisms.....                       | 289 |
| 10.3.1 | Device Configuration .....                                 | 290 |
| 10.3.2 | Resource Management.....                                   | 292 |
| 10.3.3 | Data Transfers.....                                        | 292 |
| 10.3.4 | Common Data Definitions .....                              | 293 |
| 10.4   | Host Controller Driver .....                               | 293 |
| 10.5   | Universal Serial Bus Driver .....                          | 294 |
| 10.5.1 | USBD Overview.....                                         | 294 |
| 10.5.2 | USBD Command Mechanism Requirements .....                  | 296 |
| 10.5.3 | USBD Pipe Mechanisms .....                                 | 298 |
| 10.5.4 | Managing the USB via the USBD Mechanisms.....              | 300 |
| 10.5.5 | Passing USB Preboot Control to the Operating System .....  | 302 |
| 10.6   | Operating System Environment Guides .....                  | 302 |
| 11     | Chapter 11 Hub Specification .....                         | 303 |
| 11.1   | Overview .....                                             | 303 |
| 11.1.1 | Hub Architecture.....                                      | 303 |
| 11.1.2 | Hub Connectivity .....                                     | 304 |
| 11.2   | Hub Frame/Microframe Timer.....                            | 306 |
| 11.2.1 | High-speed Microframe Timer Range.....                     | 306 |
| 11.2.2 | Full-speed Frame Timer Range .....                         | 306 |
| 11.2.3 | Frame/Microframe Timer Synchronization.....                | 307 |
| 11.2.4 | Microframe Jitter Related to Frame Jitter .....            | 309 |
| 11.2.5 | EOF1 and EOF2 Timing Points .....                          | 309 |
| 11.3   | Host Behavior at End-of-Frame.....                         | 312 |
| 11.3.1 | Full-/low-speed Latest Host Packet.....                    | 312 |
| 11.3.2 | Full-/low-speed Packet Nullification .....                 | 312 |
| 11.3.3 | Full-/low-speed Transaction Completion Prediction.....     | 313 |
| 11.4   | Internal Port.....                                         | 313 |
| 11.4.1 | Inactive.....                                              | 314 |
| 11.4.2 | Suspend Delay .....                                        | 314 |
| 11.4.3 | Full Suspend (Fsus) .....                                  | 314 |
| 11.4.4 | Generate Resume (GResume).....                             | 314 |
| 11.5   | Downstream Facing Ports .....                              | 315 |
| 11.5.1 | Downstream Facing Port State Descriptions .....            | 317 |
| 11.5.2 | Disconnect Detect Timer.....                               | 321 |
| 11.5.3 | Port Indicator.....                                        | 322 |
| 11.6   | Upstream Facing Port .....                                 | 324 |
| 11.6.1 | Full-speed .....                                           | 324 |
| 11.6.2 | High-speed .....                                           | 325 |
| 11.6.3 | Receiver .....                                             | 325 |
| 11.6.4 | Transmitter .....                                          | 328 |
| 11.7   | Hub Repeater .....                                         | 330 |
| 11.7.1 | High-speed Packet Connectivity .....                       | 330 |
| 11.7.2 | Hub Repeater State Machine.....                            | 332 |
| 11.7.3 | Wait for Start of Packet from Upstream Port (WFSOPFU)..... | 334 |

|         |                                                                   |     |
|---------|-------------------------------------------------------------------|-----|
| 11.7.4  | Wait for End of Packet from Upstream Port (WFEOPFU) .....         | 334 |
| 11.7.5  | Wait for Start of Packet (WFSOP) .....                            | 334 |
| 11.7.6  | Wait for End of Packet (WFEOP) .....                              | 334 |
| 11.8    | Bus State Evaluation .....                                        | 335 |
| 11.8.1  | Port Error .....                                                  | 335 |
| 11.8.2  | Speed Detection .....                                             | 335 |
| 11.8.3  | Collision .....                                                   | 336 |
| 11.8.4  | Low-speed Port Behavior .....                                     | 336 |
| 11.9    | Suspend and Resume .....                                          | 337 |
| 11.10   | Hub Reset Behavior .....                                          | 339 |
| 11.11   | Hub Port Power Control .....                                      | 339 |
| 11.11.1 | Multiple Gangs .....                                              | 340 |
| 11.12   | Hub Controller .....                                              | 340 |
| 11.12.1 | Endpoint Organization .....                                       | 341 |
| 11.12.2 | Hub Information Architecture and Operation .....                  | 341 |
| 11.12.3 | Port Change Information Processing .....                          | 342 |
| 11.12.4 | Hub and Port Status Change Bitmap .....                           | 343 |
| 11.12.5 | Over-current Reporting and Recovery .....                         | 344 |
| 11.12.6 | Enumeration Handling .....                                        | 345 |
| 11.13   | Hub Configuration .....                                           | 345 |
| 11.14   | Transaction Translator .....                                      | 346 |
| 11.14.1 | Overview .....                                                    | 347 |
| 11.14.2 | Transaction Translator Scheduling .....                           | 349 |
| 11.15   | Split Transaction Notation Information .....                      | 351 |
| 11.16   | Common Split Transaction State Machines .....                     | 354 |
| 11.16.1 | Host Controller State Machine .....                               | 355 |
| 11.16.2 | Transaction Translator State Machine .....                        | 359 |
| 11.17   | Bulk/Control Transaction Translation Overview .....               | 364 |
| 11.17.1 | Bulk/Control Split Transaction Sequences .....                    | 365 |
| 11.17.2 | Bulk/Control Split Transaction State Machines .....               | 371 |
| 11.17.3 | Bulk/Control Sequencing .....                                     | 376 |
| 11.17.4 | Bulk/Control Buffering Requirements .....                         | 377 |
| 11.17.5 | Other Bulk/Control Details .....                                  | 377 |
| 11.18   | Periodic Split Transaction Pipelining and Buffer Management ..... | 377 |
| 11.18.1 | Best Case Full-Speed Budget .....                                 | 378 |
| 11.18.2 | TT Microframe Pipeline .....                                      | 378 |
| 11.18.3 | Generation of Full-speed Frames .....                             | 379 |
| 11.18.4 | Host Split Transaction Scheduling Requirements .....              | 379 |
| 11.18.5 | TT Response Generation .....                                      | 382 |
| 11.18.6 | TT Periodic Transaction Handling Requirements .....               | 383 |
| 11.18.7 | TT Transaction Tracking .....                                     | 385 |
| 11.18.8 | TT Complete-split Transaction State Searching .....               | 386 |
| 11.19   | Approximate TT Buffer Space Required .....                        | 387 |
| 11.20   | Interrupt Transaction Translation Overview .....                  | 387 |
| 11.20.1 | Interrupt Split Transaction Sequences .....                       | 388 |
| 11.20.2 | Interrupt Split Transaction State Machines .....                  | 391 |
| 11.20.3 | Interrupt OUT Sequencing .....                                    | 397 |
| 11.20.4 | Interrupt IN Sequencing .....                                     | 398 |
| 11.21   | Isochronous Transaction Translation Overview .....                | 399 |

|            |                                                                  |     |
|------------|------------------------------------------------------------------|-----|
| 11.21.1    | Isochronous Split Transaction Sequences .....                    | 400 |
| 11.21.2    | Isochronous Split Transaction State Machines .....               | 403 |
| 11.21.3    | Isochronous OUT Sequencing .....                                 | 406 |
| 11.21.4    | Isochronous IN Sequencing .....                                  | 407 |
| 11.22      | TT Error Handling .....                                          | 408 |
| 11.22.1    | Loss of TT Synchronization With HS SOFs .....                    | 408 |
| 11.22.2    | TT Frame and Microframe Timer Synchronization Requirements ..... | 409 |
| 11.23      | Descriptors .....                                                | 410 |
| 11.23.1    | Standard Descriptors for Hub Class .....                         | 411 |
| 11.23.2    | Class-specific Descriptors .....                                 | 419 |
| 11.24      | Requests .....                                                   | 420 |
| 11.24.1    | Standard Requests .....                                          | 420 |
| 11.24.2    | Class-specific Requests .....                                    | 421 |
| Appendix A | Transaction Examples .....                                       | 437 |
| A.1        | Bulk/Control OUT and SETUP Transaction Examples .....            | 437 |
| A.2        | Bulk/Control IN Transaction Examples .....                       | 461 |
| A.3        | Interrupt OUT Transaction Examples .....                         | 485 |
| A.4        | Interrupt IN Transaction Examples .....                          | 504 |
| A.5        | Isochronous OUT Split-transaction Examples.....                  | 526 |
| A.6        | Isochronous IN Split-transaction Examples .....                  | 535 |
| Appendix B | Example Declarations for State Machines .....                    | 549 |
| B.1        | Global Declarations .....                                        | 550 |
| B.2        | Host Controller Declarations .....                               | 553 |
| B.3        | Transaction Translator Declarations.....                         | 555 |
| Appendix C | Reset Protocol State Diagrams .....                              | 559 |
| C.1        | Downstream Facing Port State Diagram.....                        | 559 |
| C.2        | Upstream Facing Port State Diagram .....                         | 561 |
| C.2.1      | Reset From Suspended State .....                                 | 561 |
| C.2.2      | Reset From Full-speed Non-suspended State .....                  | 564 |
| C.2.3      | Reset From High-speed Non-suspended State .....                  | 564 |
| C.2.4      | Reset Handshake .....                                            | 564 |
| Figure 3-1 | – Application Space Taxonomy .....                               | 37  |
| Figure 4-1 | – Bus Topology .....                                             | 41  |
| Figure 4-2 | – USB Cable .....                                                | 42  |
| Figure 4-3 | – A Typical Hub .....                                            | 47  |
| Figure 4-4 | – Hubs in a Desktop Computer Environment .....                   | 48  |
| Figure 5-1 | – Simple USB Host/Device View .....                              | 50  |
| Figure 5-2 | – USB Implementation Areas .....                                 | 51  |
| Figure 5-3 | – Host Composition.....                                          | 52  |
| Figure 5-4 | – Physical Device Composition .....                              | 53  |
| Figure 5-5 | – USB Physical Bus Topology .....                                | 53  |
| Figure 5-6 | – Multiple Full-speed Buses in a High-speed System .....         | 54  |
| Figure 5-7 | – USB Logical Bus Topology .....                                 | 55  |
| Figure 5-8 | – Client Software-to-function Relationships .....                | 55  |
| Figure 5-9 | – USB Host/Device Detailed View .....                            | 56  |

|                                                                                               |     |
|-----------------------------------------------------------------------------------------------|-----|
| Figure 5-10 – USB Communication Flow .....                                                    | 57  |
| Figure 5-11 – Data Phase PID Sequence for Isochronous IN High Bandwidth Endpoints.....        | 78  |
| Figure 5-12 – Data Phase PID Sequence for Isochronous OUT High Bandwidth<br>Endpoints .....   | 79  |
| Figure 5-13 – USB Information Conversion From Client Software to Bus.....                     | 80  |
| Figure 5-14 – Transfers for Communication Flows .....                                         | 83  |
| Figure 5-15 – Arrangement of IRPs to Transactions/(Micro)frames .....                         | 84  |
| Figure 5-16 – Non-USB Isochronous Example .....                                               | 88  |
| Figure 5-17 – USB Full-speed Isochronous Application .....                                    | 90  |
| Figure 5-18 – Example Source/Sink Connectivity .....                                          | 96  |
| Figure 5-19 – Data Prebuffering.....                                                          | 100 |
| Figure 5-20 – Packet and Buffer Size Formulas for Rate-matched Isochronous<br>Transfers ..... | 102 |
| Figure 6-1 – Keyed Connector Protocol .....                                                   | 103 |
| Figure 6-2 – USB Standard Detachable Cable Assembly .....                                     | 105 |
| Figure 6-3 – USB High-/full-speed Hardwired Cable Assembly .....                              | 107 |
| Figure 6-4 – USB Low-speed Hardwired Cable Assembly .....                                     | 109 |
| Figure 6-5 – USB Icon .....                                                                   | 111 |
| Figure 6-6 – Typical USB Plug Orientation.....                                                | 111 |
| Figure 6-7 – USB Series "A" Receptacle Interface and Mating Drawing .....                     | 113 |
| Figure 6-8 – USB Series "B" Receptacle Interface and Mating Drawing .....                     | 114 |
| Figure 6-9 – USB Series "A" Plug Interface Drawing .....                                      | 116 |
| Figure 6-10 – USB Series "B" Plug Interface Drawing .....                                     | 117 |
| Figure 6-11 – Typical High-/full-speed Cable Construction.....                                | 119 |
| Figure 6-12 – Single Pin-type Series "A" Receptacle.....                                      | 129 |
| Figure 6-13 – Dual Pin-type Series "A" Receptacle .....                                       | 130 |
| Figure 6-14 – Single Pin-type Series "B" Receptacle.....                                      | 131 |
| Figure 7-1 – Example High-speed Capable Transceiver Circuit.....                              | 132 |
| Figure 7-2 – Maximum Input Waveforms for USB Signaling .....                                  | 135 |
| Figure 7-3 – Example Full-speed CMOS Driver Circuit (non High-speed capable).....             | 136 |
| Figure 7-4 – Full-speed Buffer V/I Characteristics .....                                      | 138 |
| Figure 7-5 – Full-speed Buffer V/I Characteristics for High-speed Capable Transceiver .....   | 139 |
| Figure 7-6 – Full-speed Signal Waveforms.....                                                 | 140 |
| Figure 7-7 – Low-speed Driver Signal Waveforms.....                                           | 140 |
| Figure 7-8 – Data Signal Rise and Fall Time .....                                             | 142 |
| Figure 7-9 – Full-speed Load .....                                                            | 143 |
| Figure 7-10 – Low-speed Port Loads .....                                                      | 143 |
| Figure 7-11 – Measurement Planes .....                                                        | 143 |
| Figure 7-12 – Transmitter/Receiver Test Fixture .....                                         | 144 |
| Figure 7-13 – Template 1.....                                                                 | 145 |
| Figure 7-14 – Template 2.....                                                                 | 146 |
| Figure 7-15 – Template 3.....                                                                 | 147 |
| Figure 7-16 – Template 4.....                                                                 | 148 |
| Figure 7-17 – Template 5.....                                                                 | 149 |

|                                                                                                        |     |
|--------------------------------------------------------------------------------------------------------|-----|
| Figure 7-18 – Template 6.....                                                                          | 150 |
| Figure 7-19 – Differential Input Sensitivity Range for Low-/full-speed.....                            | 152 |
| Figure 7-20 – Full-speed Device Cable and Resistor Connections .....                                   | 153 |
| Figure 7-21 – Low-speed Device Cable and Resistor Connections.....                                     | 154 |
| Figure 7-22 – Placement of Optional Edge Rate Control Capacitors for Low-/full-speed.....              | 155 |
| Figure 7-23 – Diagram for High-speed Loading Equivalent Circuit.....                                   | 155 |
| Figure 7-24 – Upstream Facing Full-speed Port Transceiver .....                                        | 159 |
| Figure 7-25 – Downstream Facing Low-/full-speed Port Transceiver .....                                 | 159 |
| Figure 7-26 – Low-/full-speed Disconnect Detection.....                                                | 162 |
| Figure 7-27 – Full-/high-speed Device Connect Detection.....                                           | 162 |
| Figure 7-28 – Low-speed Device Connect Detection .....                                                 | 162 |
| Figure 7-29 – Power-on and Connection Events Timing .....                                              | 163 |
| Figure 7-30 – Low-/full-speed Packet Voltage Levels .....                                              | 165 |
| Figure 7-31 – NRZI Data Encoding .....                                                                 | 170 |
| Figure 7-32 – Bit Stuffing .....                                                                       | 171 |
| Figure 7-33 – Illustration of Extra Bit Preceding EOP (Full-/low-speed).....                           | 171 |
| Figure 7-34 – Flow Diagram for Bit Stuffing.....                                                       | 172 |
| Figure 7-35 – Sync Pattern (Low-/full-speed) .....                                                     | 172 |
| Figure 7-36 – Data Jitter Taxonomy .....                                                               | 174 |
| Figure 7-37 – SE0 for EOP Width Timing .....                                                           | 175 |
| Figure 7-38 – Hub Propagation Delay of Full-speed Differential Signals.....                            | 176 |
| Figure 7-39 – Full-speed Cable Delay .....                                                             | 180 |
| Figure 7-40 – Low-speed Cable Delay .....                                                              | 180 |
| Figure 7-41 – Worst-case End-to-end Signal Delay Model for Low-/full-speed.....                        | 183 |
| Figure 7-42 – Compound Bus-powered Hub.....                                                            | 186 |
| Figure 7-43 – Compound Self-powered Hub.....                                                           | 187 |
| Figure 7-44 – Low-power Bus-powered Function.....                                                      | 188 |
| Figure 7-45 – High-power Bus-powered Function.....                                                     | 188 |
| Figure 7-46 – Self-powered Function .....                                                              | 189 |
| Figure 7-47 – Worst-case Voltage Drop Topology (Steady State).....                                     | 189 |
| Figure 7-48 – Typical Suspend Current Averaging Profile .....                                          | 190 |
| Figure 7-49 – Differential Data Jitter for Low-/full-speed .....                                       | 202 |
| Figure 7-50 – Differential-to-EOP Transition Skew and EOP Width for Low-/full-speed .....              | 202 |
| Figure 7-51 – Receiver Jitter Tolerance for Low-/full-speed .....                                      | 202 |
| Figure 7-52 – Hub Differential Delay, Differential Jitter, and SOP Distortion for Low-/full-speed..... | 203 |
| Figure 7-53 – Hub EOP Delay and EOP Skew for Low-/full-speed.....                                      | 204 |
| Figure 8-1 – PID Format .....                                                                          | 205 |
| Figure 8-2 – ADDR Field.....                                                                           | 207 |
| Figure 8-3 – Endpoint Field.....                                                                       | 207 |
| Figure 8-4 – Data Field Format .....                                                                   | 208 |
| Figure 8-5 – Token Format .....                                                                        | 209 |
| Figure 8-6 – Packets in a Start-split Transaction.....                                                 | 210 |

|                                                                                                 |     |
|-------------------------------------------------------------------------------------------------|-----|
| Figure 8-7 – Packets in a Complete-split Transaction .....                                      | 210 |
| Figure 8-8 – Relationship of Interrupt IN Transaction to High-speed Split Transaction .....     | 211 |
| Figure 8-9 – Relationship of Interrupt OUT Transaction to High-speed Split OUT Transaction..... | 211 |
| Figure 8-10 – Start-split (SSPLIT) Token .....                                                  | 212 |
| Figure 8-11 – Port Field .....                                                                  | 212 |
| Figure 8-12 – Complete-split (CSPLIT) Transaction Token.....                                    | 214 |
| Figure 8-13 – SOF Packet .....                                                                  | 214 |
| Figure 8-14 – Relationship between Frames and Microframes .....                                 | 215 |
| Figure 8-15 – Data Packet Format .....                                                          | 216 |
| Figure 8-16 – Handshake Packet .....                                                            | 216 |
| Figure 8-17 – Legend for State Machines.....                                                    | 219 |
| Figure 8-18 – State Machine Context Overview.....                                               | 220 |
| Figure 8-19 – Host Controller Top Level Transaction State Machine Hierarchy Overview .....      | 220 |
| Figure 8-20 – Host Controller Non-split Transaction State Machine Hierarchy Overview .....      | 221 |
| Figure 8-21 – Device Transaction State Machine Hierarchy Overview.....                          | 221 |
| Figure 8-22 – Device Top Level State Machine .....                                              | 222 |
| Figure 8-23 – Device_process_Trans State Machine.....                                           | 223 |
| Figure 8-24 – Dev_do_OUT State Machine .....                                                    | 224 |
| Figure 8-25 – Dev_do_IN State Machine.....                                                      | 225 |
| Figure 8-26 – HC_Do_nonsplit State Machine.....                                                 | 226 |
| Figure 8-27 – Host High-speed Bulk OUT/Control Ping State Machine .....                         | 228 |
| Figure 8-28 – Dev_HS_ping State Machine.....                                                    | 229 |
| Figure 8-29 – Device High-speed Bulk OUT /Control State Machine .....                           | 230 |
| Figure 8-30 – Bulk Transaction Format .....                                                     | 231 |
| Figure 8-31 – Bulk/Control/Interrupt OUT Transaction Host State Machine .....                   | 232 |
| Figure 8-32 – Bulk/Control/Interrupt OUT Transaction Device State Machine.....                  | 233 |
| Figure 8-33 – Bulk/Control/Interrupt IN Transaction Host State Machine .....                    | 234 |
| Figure 8-34 – Bulk/Control/Interrupt IN Transaction Device State Machine.....                   | 235 |
| Figure 8-35 – Bulk Reads and Writes .....                                                       | 235 |
| Figure 8-36 – Control SETUP Transaction .....                                                   | 236 |
| Figure 8-37 – Control Read and Write Sequences.....                                             | 237 |
| Figure 8-38 – Interrupt Transaction Format.....                                                 | 239 |
| Figure 8-39 – Isochronous Transaction Format .....                                              | 240 |
| Figure 8-40 – Isochronous OUT Transaction Host State Machine.....                               | 241 |
| Figure 8-41 – Isochronous OUT Transaction Device State Machine .....                            | 241 |
| Figure 8-42 – Isochronous IN Transaction Host State Machine .....                               | 242 |
| Figure 8-43 – Isochronous IN Transaction Device State Machine .....                             | 243 |
| Figure 8-44 – SETUP Initialization .....                                                        | 244 |
| Figure 8-45 – Consecutive Transactions .....                                                    | 244 |
| Figure 8-46 – NAKed Transaction with Retry.....                                                 | 245 |
| Figure 8-47 – Corrupted ACK Handshake with Retry.....                                           | 245 |
| Figure 8-48 – Low-speed Transaction .....                                                       | 246 |

|                                                                                                         |     |
|---------------------------------------------------------------------------------------------------------|-----|
| Figure 8-49 – Bus Turn-around Timer Usage .....                                                         | 248 |
| Figure 9-1 – Device State Diagram .....                                                                 | 251 |
| Figure 9-2 – wIndex Format when Specifying an Endpoint .....                                            | 260 |
| Figure 9-3 – wIndex Format when Specifying an Interface .....                                           | 260 |
| Figure 9-4 – Information Returned by a GetStatus() Request to a Device.....                             | 265 |
| Figure 9-5 – Information Returned by a GetStatus() Request to an Interface.....                         | 265 |
| Figure 9-6 – Information Returned by a GetStatus() Request to an Endpoint.....                          | 265 |
| Figure 9-7 – Example of Feedback Endpoint Numbers .....                                                 | 279 |
| Figure 9-8 – Example of Feedback Endpoint Relationships .....                                           | 279 |
| Figure 10-1 – Interlayer Communications Model .....                                                     | 282 |
| Figure 10-2 – Host Communications .....                                                                 | 283 |
| Figure 10-3 – Frame and Microframe Creation .....                                                       | 287 |
| Figure 10-4 – Configuration Interactions .....                                                          | 290 |
| Figure 10-5 – Universal Serial Bus Driver Structure .....                                               | 295 |
| Figure 11-1 – Hub Architecture .....                                                                    | 304 |
| Figure 11-2 – Hub Signaling Connectivity .....                                                          | 305 |
| Figure 11-3 – Resume Connectivity .....                                                                 | 305 |
| Figure 11-4 – Example High-speed EOF Offsets Due to Propagation Delay Without<br>EOF Advancement.....   | 308 |
| Figure 11-5 – Example High-speed EOF Offsets Due to Propagation Delay With EOF<br>Advancement.....      | 308 |
| Figure 11-6 – High-speed EOF2 Timing Point .....                                                        | 310 |
| Figure 11-7 – High-speed EOF1 Timing Point .....                                                        | 310 |
| Figure 11-8 – Full-speed EOF Timing Points.....                                                         | 310 |
| Figure 11-9 – Internal Port State Machine.....                                                          | 314 |
| Figure 11-10 – Downstream Facing Hub Port State Machine.....                                            | 316 |
| Figure 11-11 – Port Indicator State Diagram .....                                                       | 323 |
| Figure 11-12 – Upstream Facing Port Receiver State Machine.....                                         | 325 |
| Figure 11-13 – Upstream Facing Port Transmitter State Machine.....                                      | 328 |
| Figure 11-14 – Example Hub Repeater Organization.....                                                   | 330 |
| Figure 11-15 – High-speed Port Selector State Machine .....                                             | 331 |
| Figure 11-16 – Hub Repeater State Machine .....                                                         | 333 |
| Figure 11-17 – Example Remote-wakeup Resume Signaling With Full-/low-speed<br>Device .....              | 338 |
| Figure 11-18 – Example Remote-wakeup Resume Signaling With High-speed Device .....                      | 338 |
| Figure 11-19 – Example Hub Controller Organization.....                                                 | 341 |
| Figure 11-20 – Relationship of Status, Status Change, and Control Information to<br>Device States ..... | 342 |
| Figure 11-21 – Port Status Handling Method.....                                                         | 343 |
| Figure 11-22 – Hub and Port Status Change Bitmap .....                                                  | 344 |
| Figure 11-23 – Example Hub and Port Change Bit Sampling.....                                            | 344 |
| Figure 11-24 – Transaction Translator Overview .....                                                    | 347 |
| Figure 11-25 – Periodic and Non-periodic Buffer Sections of TT .....                                    | 348 |
| Figure 11-26 – TT Microframe Pipeline for Periodic Split Transactions.....                              | 349 |



|                                                                                           |     |
|-------------------------------------------------------------------------------------------|-----|
| Figure 11-27 – TT Nonperiodic Buffering .....                                             | 350 |
| Figure 11-28 – Example Full-/low-speed Handler Scheduling for Start-splits .....          | 351 |
| Figure 11-29 – Flow Sequence Legend .....                                                 | 351 |
| Figure 11-30 – Legend for State Machines .....                                            | 352 |
| Figure 11-31 – State Machine Context Overview .....                                       | 354 |
| Figure 11-32 – Host Controller Split Transaction State Machine Hierarchy Overview .....   | 354 |
| Figure 11-33 – Transaction Translator State Machine Hierarchy Overview .....              | 355 |
| Figure 11-34 – Host Controller .....                                                      | 355 |
| Figure 11-35 – HC_Process_Command .....                                                   | 356 |
| Figure 11-36 – HC_Do_Start .....                                                          | 357 |
| Figure 11-37 – HC_Do_Complete .....                                                       | 358 |
| Figure 11-38 – Transaction Translator .....                                               | 359 |
| Figure 11-39 – TT_Process_Packet .....                                                    | 360 |
| Figure 11-40 – TT_Do_Start .....                                                          | 361 |
| Figure 11-41 – TT_Do_Complete .....                                                       | 362 |
| Figure 11-42 – TT_BulkSS .....                                                            | 362 |
| Figure 11-43 – TT_BulkCS .....                                                            | 363 |
| Figure 11-44 – TT_IntSS .....                                                             | 363 |
| Figure 11-45 – TT_IntCS .....                                                             | 364 |
| Figure 11-46 – TT_IsochSS .....                                                           | 364 |
| Figure 11-47 – Sample Algorithm for Compare_buffs .....                                   | 366 |
| Figure 11-48 – Bulk/Control OUT Start-split Transaction Sequence .....                    | 367 |
| Figure 11-49 – Bulk/Control OUT Complete-split Transaction Sequence .....                 | 368 |
| Figure 11-50 – Bulk/Control IN Start-split Transaction Sequence .....                     | 369 |
| Figure 11-51 – Bulk/Control IN Complete-split Transaction Sequence .....                  | 370 |
| Figure 11-52 – Bulk/Control OUT Start-split Transaction Host State Machine .....          | 371 |
| Figure 11-53 – Bulk/Control OUT Complete-split Transaction Host State Machine .....       | 372 |
| Figure 11-54 – Bulk/Control OUT Start-split Transaction TT State Machine .....            | 373 |
| Figure 11-55 – Bulk/Control OUT Complete-split Transaction TT State Machine .....         | 373 |
| Figure 11-56 – Bulk/Control IN Start-split Transaction Host State Machine .....           | 374 |
| Figure 11-57 – Bulk/Control IN Complete-split Transaction Host State Machine .....        | 375 |
| Figure 11-58 – Bulk/Control IN Start-split Transaction TT State Machine .....             | 376 |
| Figure 11-59 – Bulk/Control IN Complete-split Transaction TT State Machine .....          | 376 |
| Figure 11-60 – Best Case Budgeted Full-speed Wire Time With No Bit Stuffing .....         | 378 |
| Figure 11-61 – Scheduling of TT Microframe Pipeline .....                                 | 379 |
| Figure 11-62 – Isochronous OUT Example That Avoids a Start-split-end With Zero Data ..... | 380 |
| Figure 11-63 – End of Frame TT Pipeline Scheduling Example .....                          | 381 |
| Figure 11-64 – Isochronous IN Complete-split Schedule Example at $L=Y_6$ .....            | 381 |
| Figure 11-65 – Isochronous IN Complete-split Schedule Example at $L=Y_7$ .....            | 382 |
| Figure 11-66 – Microframe Pipeline .....                                                  | 385 |
| Figure 11-67 – Advance_Pipeline Pseudocode .....                                          | 386 |
| Figure 11-68 – Interrupt OUT Start-split Transaction Sequence .....                       | 388 |

|                                                                                   |     |
|-----------------------------------------------------------------------------------|-----|
| Figure 11-69 – Interrupt OUT Complete-split Transaction Sequence .....            | 389 |
| Figure 11-70 – Interrupt IN Start-split Transaction Sequence .....                | 389 |
| Figure 11-71 – Interrupt IN Complete-split Transaction Sequence.....              | 390 |
| Figure 11-72 – Interrupt OUT Start-split Transaction Host State Machine .....     | 391 |
| Figure 11-73 – Interrupt OUT Complete-split Transaction Host State Machine .....  | 392 |
| Figure 11-74 – Interrupt OUT Start-split Transaction TT State Machine .....       | 393 |
| Figure 11-75 – Interrupt OUT Complete-split Transaction TT State Machine .....    | 393 |
| Figure 11-76 – Interrupt IN Start-split Transaction Host State Machine .....      | 394 |
| Figure 11-77 – Interrupt IN Complete-split Transaction Host State Machine .....   | 395 |
| Figure 11-78 – HC_Data_or_Error State Machine .....                               | 396 |
| Figure 11-79 – Interrupt IN Start-split Transaction TT State Machine .....        | 396 |
| Figure 11-80 – Interrupt IN Complete-split Transaction TT State Machine.....      | 397 |
| Figure 11-81 – Example of CRC16 Handling for Interrupt OUT.....                   | 398 |
| Figure 11-82 – Example of CRC16 Handling for Interrupt IN .....                   | 399 |
| Figure 11-83 – Isochronous OUT Start-split Transaction Sequence .....             | 401 |
| Figure 11-84 – Isochronous IN Start-split Transaction Sequence .....              | 401 |
| Figure 11-85 – Isochronous IN Complete-split Transaction Sequence.....            | 402 |
| Figure 11-86 – Isochronous OUT Start-split Transaction Host State Machine.....    | 403 |
| Figure 11-87 – Isochronous OUT Start-split Transaction TT State Machine.....      | 404 |
| Figure 11-88 – Isochronous IN Start-split Transaction Host State Machine .....    | 405 |
| Figure 11-89 – Isochronous IN Complete-split Transaction Host State Machine ..... | 405 |
| Figure 11-90 – Isochronous IN Start-split Transaction TT State Machine .....      | 406 |
| Figure 11-91 – Isochronous IN Complete-split Transaction TT State Machine .....   | 406 |
| Figure 11-92 – Example of CRC16 Isochronous OUT Data Packet Handling .....        | 407 |
| Figure 11-93 – Example of CRC16 Isochronous IN Data Packet Handling.....          | 408 |
| Figure 11-94 – Example Frame/Microframe Synchronization Events .....              | 410 |
| Figure A-1 – Normal No Smash .....                                                | 438 |
| Figure A-2 – Normal HS DATA0/1 Smash .....                                        | 439 |
| Figure A-3 – Normal HS DATA0/1 3 Strikes Smash.....                               | 440 |
| Figure A-4 – Normal HS ACK(S) Smash (case 1).....                                 | 441 |
| Figure A-5 – Normal HS ACK(S) Smash (case 2).....                                 | 442 |
| Figure A-6 – Normal HS ACK(S) 3 Strikes Smash.....                                | 443 |
| Figure A-7 – Normal HS CSPLIT Smash .....                                         | 444 |
| Figure A-8 – Normal HS CSPLIT 3 Strikes Smash .....                               | 445 |
| Figure A-9 – Normal HS ACK(C) Smash .....                                         | 446 |
| Figure A-10 – Normal S ACK(C) 3 Strikes Smash .....                               | 447 |
| Figure A-11 – Normal FS/LS DATA0/1 Smash .....                                    | 448 |
| Figure A-12 – Normal FS/LS DATA0/1 3 Strikes Smash.....                           | 449 |
| Figure A-13 – Normal FS/LS ACK Smash .....                                        | 450 |
| Figure A-14 – Normal FS/LS ACK 3 Strikes Smash.....                               | 451 |
| Figure A-15 – No buffer Available No Smash (HS NAK(S)) .....                      | 452 |
| Figure A-16 – No Buffer Available HS NAK(S) Smash.....                            | 453 |
| Figure A-17 – No Buffer Available HS NAK(S) 3 Strikes Smash .....                 | 454 |

|                                                                                               |     |
|-----------------------------------------------------------------------------------------------|-----|
| Figure A-18 – CS Earlier No Smash (HS NYET).....                                              | 455 |
| Figure A-19 – CS Earlier HS NYET Smash (case 1).....                                          | 456 |
| Figure A-20 – CS Earlier HS NYET Smash (case 2).....                                          | 457 |
| Figure A-21 – CS Earlier HS NYET 3 Strikes Smash.....                                         | 458 |
| Figure A-22 – Device Busy No Smash(FS/LS NAK).....                                            | 459 |
| Figure A-23 – Device Stall No Smash(FS/LS STALL).....                                         | 460 |
| Figure A-24 – Normal No Smash.....                                                            | 462 |
| Figure A-25 – Normal HS SSPLIT Smash .....                                                    | 463 |
| Figure A-26 – Normal SSPLIT 3 Strikes Smash .....                                             | 464 |
| Figure A-27 – Normal HS ACK(S) Smash (case 1).....                                            | 465 |
| Figure A-28 – Normal HS ACK(S) Smash (case 2).....                                            | 466 |
| Figure A-29 – Normal HS ACK(S) 3 Strikes Smash.....                                           | 467 |
| Figure A-30 – Normal HS CSPLIT Smash .....                                                    | 468 |
| Figure A-31 – Normal HS CSPLIT 3 Strikes Smash.....                                           | 469 |
| Figure A-32 – Normal HS DATA0/1 Smash .....                                                   | 470 |
| Figure A-33 – Normal HS DATA0/1 3 Strikes Smash.....                                          | 471 |
| Figure A-34 – Normal FS/LS IN Smash.....                                                      | 472 |
| Figure A-35 – Normal FS/LS IN 3 Strikes Smash .....                                           | 473 |
| Figure A-36 – Normal FS/LS DATA0/1 Smash .....                                                | 474 |
| Figure A-37 – Normal FS/LS DATA0/1 3 Strikes Smash.....                                       | 475 |
| Figure A-38 – Normal FS/LS ACK Smash .....                                                    | 476 |
| Figure A-39 – No Buffer Available No Smash(HS NAK(S)).....                                    | 477 |
| Figure A-40 – No Buffer Available HS NAK(S) Smash.....                                        | 478 |
| Figure A-41 – No Buffer Available HS NAK(S) 3 Strikes Smash .....                             | 479 |
| Figure A-42 – CS Earlier No Smash (HS NYET).....                                              | 480 |
| Figure A-43 – CS Earlier HS NYET Smash (case 1).....                                          | 481 |
| Figure A-44 – CS Earlier HS NYET Smash (case 2).....                                          | 482 |
| Figure A-45 – Device Busy No Smash(FS/LS NAK).....                                            | 483 |
| Figure A-46 – Device Stall No Smash(FS/LS STALL).....                                         | 484 |
| Figure A-47 – Normal No Smash(FS/LS Handshake Packet is Done by M+1).....                     | 487 |
| Figure A-48 – Normal HS DATA0/1 Smash .....                                                   | 488 |
| Figure A-49 – Normal HS CSPLIT Smash .....                                                    | 489 |
| Figure A-50 – Normal HS CSPLIT 3 Strikes Smash.....                                           | 490 |
| Figure A-51 – Normal HS ACK(C) Smash .....                                                    | 491 |
| Figure A-52 – Normal HS ACK(C) 3 Strikes Smash.....                                           | 492 |
| Figure A-53 – Normal FS/LS DATA0/1 Smash .....                                                | 493 |
| Figure A-54 – Normal FS/LS ACK Smash .....                                                    | 494 |
| Figure A-55 – Searching No Smash .....                                                        | 495 |
| Figure A-56 – CS Earlier No Smash(HS NYET and FS/LS Handshake Packet is Done<br>by M+2) ..... | 496 |
| Figure A-57 – CS Earlier No Smash(HS NYET and FS/LS Handshake Packet is Done<br>by M+3) ..... | 497 |
| Figure A-58 – CS Earlier HS NYET Smash .....                                                  | 498 |
| Figure A-59 – CS Earlier HS NYET 3 Strikes Smash.....                                         | 499 |

|                                                                                                                                  |     |
|----------------------------------------------------------------------------------------------------------------------------------|-----|
| Figure A-60 – Abort and Free Abort(FS/LS Transaction is Continued at End of M+3) .....                                           | 500 |
| Figure A-61 – Abort and Free Free(FS/LS Transaction is not Started at End of M+3) .....                                          | 501 |
| Figure A-62 – Device Busy No Smash(FS/LS NAK).....                                                                               | 502 |
| Figure A-63 – Device Stall No Smash(FS/LS STALL) .....                                                                           | 503 |
| Figure A-64 – Normal No Smash (FS/LS Data Packet is on M+1).....                                                                 | 506 |
| Figure A-65 – Normal HS SSPLIT Smash .....                                                                                       | 507 |
| Figure A-66 – Normal HS CSPLIT Smash .....                                                                                       | 508 |
| Figure A-67 – Normal HS CSPLIT 3 Strikes Smash.....                                                                              | 509 |
| Figure A-68 – Normal HS DATA0/1 Smash .....                                                                                      | 510 |
| Figure A-69 – Normal HS DATA0/1 3 Strikes Smash.....                                                                             | 511 |
| Figure A-70 – Normal FS/LS IN Smash .....                                                                                        | 512 |
| Figure A-71 – Normal FS/LS DATA0/1 Smash .....                                                                                   | 513 |
| Figure A-72 – Normal FS/LS ACK Smash .....                                                                                       | 514 |
| Figure A-73 – Searching No Smash .....                                                                                           | 515 |
| Figure A-74 – CS Earlier No Smash (HS MDATA and FS/LS Data Packet is on M+1<br>and M+2) .....                                    | 516 |
| Figure A-75 – CS Earlier No Smash (HS NYET and FS/LS Data Packet is on M+2) .....                                                | 517 |
| Figure A-76 – CS Earlier No Smash (HS NYET and MDATA and FS/LS Data Packet is<br>on M+2 and M+3).....                            | 518 |
| Figure A-77 – CS Earlier No Smash(HS NYET and FS/LS Data Packet is on M+3) .....                                                 | 519 |
| Figure A-78 – CS Earlier HS NYET Smash .....                                                                                     | 520 |
| Figure A-79 – CS Earlier HS NYET 3 Strikes Smash.....                                                                            | 521 |
| Figure A-80 – Abort and Free Abort (HS NYET and FS/LS Transaction is Continued at<br>End of M+3) .....                           | 522 |
| Figure A-81 – Abort and Free Free (HS NYET and FS/LS Transaction is not Started at<br>End of M+3) .....                          | 523 |
| Figure A-82 – Device Busy No Smash(FS/LS NAK).....                                                                               | 524 |
| Figure A-83 – Device Stall No Smash(FS/LS STALL) .....                                                                           | 525 |
| Figure C-1 – Downstream Facing Port Reset Protocol State Diagram .....                                                           | 560 |
| Figure C-2 – Upstream Facing Port Reset Detection State Diagram.....                                                             | 562 |
| Figure C-3 – Upstream Facing Port Reset Handshake State Diagram .....                                                            | 563 |
| Figure 8-27 – Host High-speed Bulk OUT/Control Ping State Machine .....                                                          | 643 |
| Figure 8-31 – FS Bulk, FS/LS <del>/</del> Control, or HS/FS/LS Interrupt <del>/</del> OUT Transaction Host<br>State Machine..... | 644 |
| Figure 8-32 – FS Bulk, <del>/</del> FS/LS Control, <del>/</del> or HS/FS/LS Interrupt OUT Transaction Host<br>State Machine..... | 645 |
| Figure 11-11 – Port Indicator State Diagram .....                                                                                | 661 |
| Figure 6-1 – Keyed Connector Protocol .....                                                                                      | 670 |
| Figure 6-2 – USB Standard Detachable Cable Assembly .....                                                                        | 672 |
| Figure 6-3 – USB Standard Mini-connector Detachable Cable Assembly.....                                                          | 673 |
| Figure 6-3 – USB High-/full-speed Hardwired Cable Assembly .....                                                                 | 675 |
| Figure <del>6-4</del> 6-5 – USB Low-speed Hardwired Cable Assembly .....                                                         | 677 |
| Figure <del>6-5</del> 6-6 – USB Icon .....                                                                                       | 679 |
| Figure <del>6-6</del> 6-7 – Typical USB Plug Orientation .....                                                                   | 680 |

|                                                                                                |     |
|------------------------------------------------------------------------------------------------|-----|
| Figure 6-8 – Typical USB “Mini-B” Connector Plug Orientation.....                              | 681 |
| Figure 6-9 – USB Series “A” Receptacle Interface and Mating Drawing .....                      | 683 |
| Figure 6-10 – USB Series “B” Receptacle Interface and Mating Drawing.....                      | 684 |
| Figure 6-11 – USB Series “Mini-B” Receptacle Interface and Mating Drawing .....                | 685 |
| Figure 6-12 – USB Series “Mini-B” Receptacle Interface Drawing (Detail).tiff .....             | 686 |
| Figure 6-13 – USB Series “A” Plug Interface Drawing .....                                      | 689 |
| Figure 6-14 – USB Series “B” Plug Interface Drawing .....                                      | 690 |
| Figure 6-15 – USB Series “Mini-B” Plug Interface Drawing.....                                  | 691 |
| Figure 6-16 – Typical High-/full-speed Cable Construction .....                                | 694 |
| Figure 6-17 – Single Pin-type Series “A” Receptacle.....                                       | 704 |
| Figure 6-18 – Dual Pin-type Series “A” Receptacle .....                                        | 705 |
| Figure 6-19 – Single Pin-type Series “B” Receptacle.....                                       | 706 |
| Figure 6-20 – Single Pin-Type Series “Mini-B” Receptacle .....                                 | 707 |
| Figure 11-11 – Port Indicator State Diagram .....                                              | 720 |
| Figure 11-82 – Example of CRC16 Handling for Interrupt IN .....                                | 725 |
| Figure 11-93 – Example of CRC16 Isochronous IN Data Packet Handling.....                       | 725 |
| Figure 6-15 – USB Series “Mini-B” Plug Interface Drawing (1 of 2) .....                        | 736 |
| Figure 6-15 – USB Series “Mini-B” Plug Interface Drawing (2 of 2) .....                        | 737 |
| Figure 1-1 – LPM State Transition Diagram .....                                                | 744 |
| Figure 2-1 – Packets in an Extension Token Transaction .....                                   | 746 |
| Figure 2-2 – LPM Extended Token .....                                                          | 747 |
| Figure 2-3 – LPM Transaction Format.....                                                       | 748 |
| Figure 4-1 – Port Control Model for Transitioning a Port to L1.....                            | 751 |
| Figure 4-2 – LPM Transaction and Transition Timing to L1 .....                                 | 752 |
| Figure 4-3 – Device Initiated L1 to L0 Transition (Remote Wake).....                           | 753 |
| Figure 4-4 – Example Remote-wakeup L1 Exit with Full-speed Device Under<br>Connected Hub ..... | 754 |
| Figure 4-5 – Basic Port Control Model for Transitioning a Port out of L1 .....                 | 757 |
| Figure 4-6 – Host Initiated L1 to L0 Transition (L1 Exit) .....                                | 757 |
| Figure 4-7 – USB 2.0 Hub Reference Port State Machine Relationships with L1<br>Additions ..... | 758 |
| Figure 4-8 – L1 Addendum to the Upstream Facing Port Receiver State Machine .....              | 759 |
| Figure 4-9 – Addendum to the Upstream Facing Port Transmitter State Machine .....              | 761 |
| Figure 4-10 – Addendum to the Internal Port State Machine .....                                | 762 |
| Figure 4-11 – Addendum to Downstream Facing Hub Port State Machine .....                       | 764 |
| Figure 7-29 – Connect Event Timing .....                                                       | 786 |
| Table 5-1 – Low-speed Control Transfer Limits .....                                            | 65  |
| Table 5-2 – Full-speed Control Transfer Limits.....                                            | 66  |
| Table 5-3 – High-speed Control Transfer Limits .....                                           | 66  |
| Table 5-4 – Full-speed Isochronous Transaction Limits.....                                     | 68  |
| Table 5-5 – High-speed Isochronous Transaction Limits .....                                    | 69  |
| Table 5-6 – Low-speed Interrupt Transaction Limits .....                                       | 72  |
| Table 5-7 – Full-speed Interrupt Transaction Limits .....                                      | 72  |

|                                                                                                    |     |
|----------------------------------------------------------------------------------------------------|-----|
| Table 5-8 – High-speed Interrupt Transaction Limits .....                                          | 73  |
| Table 5-9 – Full-speed Bulk Transaction Limits .....                                               | 76  |
| Table 5-10 – High-speed Bulk Transaction Limits .....                                              | 76  |
| Table 5-11 – <i>wMaxPacketSize</i> Field of Endpoint Descriptor .....                              | 77  |
| Table 5-12 – Synchronization Characteristics .....                                                 | 92  |
| Table 5-13 – Connection Requirements .....                                                         | 98  |
| Table 6-1 – USB Connector Termination Assignment.....                                              | 112 |
| Table 6-2 – Power Pair .....                                                                       | 120 |
| Table 6-3 – Signal Pair .....                                                                      | 120 |
| Table 6-4 – Drain Wire Signal Pair .....                                                           | 121 |
| Table 6-5 – Nominal Cable Diameter .....                                                           | 122 |
| Table 6-6 – Conductor Resistance .....                                                             | 122 |
| Table 6-7 – USB Electrical, Mechanical, and Environmental Compliance Standards .....               | 123 |
| Table 6-7 – USB Electrical, Mechanical, and Environmental Compliance Standards<br>(Continued)..... | 124 |
| Table 7-1 – Description of Functional Elements in the Example Shown in Figure 7-1 .....            | 134 |
| Table 7-2 – Low-/full-speed Signaling Levels .....                                                 | 157 |
| Table 7-3 – High-speed Signaling Levels .....                                                      | 160 |
| Table 7-3 – High-speed Signaling Levels (Continued) .....                                          | 161 |
| Table 7-4 – Full-speed Jitter Budget .....                                                         | 178 |
| Table 7-5 – Low-speed Jitter Budget.....                                                           | 179 |
| Table 7-6 – Maximum Allowable Cable Loss .....                                                     | 181 |
| Table 7-7 – DC Electrical Characteristics .....                                                    | 192 |
| Table 7-7 – DC Electrical Characteristics ( <i>Continued</i> ).....                                | 193 |
| Table 7-7 – DC Electrical Characteristics ( <i>Continued</i> ).....                                | 194 |
| Table 7-8 – High-speed Source Electrical Characteristics .....                                     | 194 |
| Table 7-9 – Full-speed Source Electrical Characteristics.....                                      | 195 |
| Table 7-10 – Low-speed Source Electrical Characteristics .....                                     | 196 |
| Table 7-11 – Hub/Repeater Electrical Characteristics .....                                         | 197 |
| Table 7-12 – Cable Characteristics (Note 14).....                                                  | 198 |
| Table 7-13 – Hub Event Timings .....                                                               | 199 |
| Table 7-13 – Hub Event Timings (Continued).....                                                    | 200 |
| Table 7-14 – Device Event Timings.....                                                             | 200 |
| Table 7-14 – Device Event Timings (Continued).....                                                 | 201 |
| Table 8-1 – PID Types .....                                                                        | 206 |
| Table 8-2 – Isochronous OUT Payload Continuation Encoding.....                                     | 213 |
| Table 8-3 – Endpoint Type Values in Split Special Token.....                                       | 214 |
| Table 8-4 – Function Responses to IN Transactions .....                                            | 217 |
| Table 8-5 – Host Responses to IN Transactions.....                                                 | 218 |
| Table 8-6 – Function Responses to OUT Transactions in Order of Precedence.....                     | 218 |
| Table 8-7 – Status Stage Responses .....                                                           | 237 |
| Table 8-8 – Packet Error Types .....                                                               | 247 |
| Table 9-1 – Visible Device States .....                                                            | 252 |

|                                                                                                          |     |
|----------------------------------------------------------------------------------------------------------|-----|
| Table 9-2 – Format of Setup Data .....                                                                   | 259 |
| Table 9-3 – Standard Device Requests .....                                                               | 261 |
| Table 9-4 – Standard Request Codes .....                                                                 | 261 |
| Table 9-5 – Descriptor Types .....                                                                       | 262 |
| Table 9-6 – Standard Feature Selectors .....                                                             | 262 |
| Table 9-7 – Test Mode Selectors .....                                                                    | 268 |
| Table 9-8 – Standard Device Descriptor .....                                                             | 271 |
| Table 9-9 – Device_Qualifier Descriptor .....                                                            | 273 |
| Table 9-10 – Standard Configuration Descriptor .....                                                     | 274 |
| Table 9-11 – Other_Speed_Configuration Descriptor .....                                                  | 275 |
| Table 9-12 – Standard Interface Descriptor .....                                                         | 276 |
| Table 9-13 – Standard Endpoint Descriptor .....                                                          | 277 |
| Table 9-13 – Standard Endpoint Descriptor ( <i>Continued</i> ) .....                                     | 278 |
| Table 9-14 – Allowed wMaxPacketSize Values for Different Numbers of Transactions<br>per Microframe ..... | 279 |
| Table 9-15 – String Descriptor Zero, Specifying Languages Supported by the Device .....                  | 280 |
| Table 9-16 – UNICODE String Descriptor .....                                                             | 280 |
| Table 11-1 – High-speed Microframe Timer Range Contributions .....                                       | 306 |
| Table 11-2 – Full-speed Frame Timer Range Contributions .....                                            | 307 |
| Table 11-3 – Hub and Host EOF1/EOF2 Timing Points .....                                                  | 309 |
| Table 11-4 – Internal Port Signal/Event Definitions .....                                                | 314 |
| Table 11-5 – Downstream Facing Port Signal/Event Definitions .....                                       | 317 |
| Table 11-6 – Automatic Port State to Port Indicator Color Mapping .....                                  | 323 |
| Table 11-7 – Port Indicator Color Definitions .....                                                      | 324 |
| Table 11-8 – Upstream Facing Port Receiver Signal/Event Definitions .....                                | 326 |
| Table 11-9 – Upstream Facing Port Transmit Signal/Event Definitions .....                                | 329 |
| Table 11-10 – High-speed Port Selector Signal/Event Definitions .....                                    | 332 |
| Table 11-11 – Hub Repeater Signal/Event Definitions .....                                                | 333 |
| Table 11-12 – Hub Power Operating Mode Summary .....                                                     | 346 |
| Table 11-13 – Hub Descriptor .....                                                                       | 419 |
| Table 11-14 – Hub Responses to Standard Device Requests .....                                            | 420 |
| Table 11-15 – Hub Class Requests .....                                                                   | 421 |
| Table 11-16 – Hub Class Request Codes .....                                                              | 422 |
| Table 11-17 – Hub Class Feature Selectors .....                                                          | 422 |
| Table 11-18 – wValue Field for Clear_TT_Buffer .....                                                     | 424 |
| Table 11-19 – Hub Status Field, wHubStatus .....                                                         | 425 |
| Table 11-20 – Hub Change Field, wHubChange .....                                                         | 426 |
| Table 11-21 – Port Status Field, wPortStatus .....                                                       | 427 |
| Table 11-22 – Port Change Field, wPortChange .....                                                       | 431 |
| Table 11-23 – Format of Returned TT State .....                                                          | 432 |
| Table 11-24 – Test Mode Selector Codes .....                                                             | 436 |
| Table 11-25 – Port Indicator Selector Codes .....                                                        | 436 |
| Table 5-3 – High-speed Control Transfer Limits .....                                                     | 636 |

|                                                                                                                    |     |
|--------------------------------------------------------------------------------------------------------------------|-----|
| Table 5-8 – High-speed Interrupt Transaction Limits .....                                                          | 637 |
| Table 5-5 – High-speed Isochronous Transaction Limits .....                                                        | 638 |
| Table 9-3 – Standard Device Requests .....                                                                         | 647 |
| Table 11-14 – Hub Responses to Standard Device Requests .....                                                      | 663 |
| Table 11-21 – Port Status Field, wPortStatus .....                                                                 | 665 |
| Table 6-1 – USB Series “A” and Series “B” Connector Termination Assignment .....                                   | 682 |
| Table 6-2 – USB Series “mini-B” Connector Termination Assignment .....                                             | 682 |
| Table <del>6-26</del> -3 – Power Pair .....                                                                        | 695 |
| Table <del>6-36</del> -4 – Signal Pair .....                                                                       | 695 |
| Table <del>6-46</del> -5 – Drain Wire Signal Pair .....                                                            | 696 |
| Table <del>6-56</del> -6 – Nominal Cable Diameter .....                                                            | 697 |
| Table <del>6-66</del> -7 – Conductor Resistance .....                                                              | 697 |
| Table <del>6-76</del> -8 – USB Electrical, Mechanical, and Environmental Compliance Standards .....                | 698 |
| Table <del>6-76</del> -8 – USB Electrical, Mechanical, and Environmental Compliance Standards<br>(Continued) ..... | 699 |
| Table <del>6-76</del> -8 – USB Electrical, Mechanical, and Environmental Compliance Standards<br>(Continued) ..... | 700 |
| Table <del>6-76</del> -8 – USB Electrical, Mechanical, and Environmental Compliance Standards<br>(Continued) ..... | 701 |
| Table <del>6-76</del> -8 – USB Electrical, Mechanical, and Environmental Compliance Standards<br>(Continued) ..... | 702 |
| Table 9-13 – Standard Endpoint Descriptor (Continued) .....                                                        | 717 |
| Table 11-6 – Automatic Port State to Port Indicator Color Mapping .....                                            | 719 |
| Table 9-5 – Descriptor Types .....                                                                                 | 733 |
| Table 9-13 – Standard Interface Association Descriptor .....                                                       | 734 |
| Table 9- <del>43</del> 14 – Standard Endpoint Descriptor .....                                                     | 734 |
| Table 9-16 – UNICODE String Descriptor .....                                                                       | 740 |
| Table 1-1 – USB Link Power Management (Lx) States .....                                                            | 743 |
| Table 1-2 – Summary Similarities/Differences Between L1 and L2 .....                                               | 744 |
| Table 2-1 – PID Types .....                                                                                        | 745 |
| Table 2-2 – SubPID Types .....                                                                                     | 747 |
| Table 2-2 – SubPID Types (cont.) .....                                                                             | 747 |
| Table 2-3 – LPM Token <i>bmAttributes</i> Field Definition .....                                                   | 748 |
| Table 3-1 – USB Device Capabilities – USB 2.0 Extension Descriptor .....                                           | 749 |
| Table 3-1 – USB Device Capabilities – USB 2.0 Extension Descriptor (cont.) .....                                   | 750 |
| Table 4-1 – Device Initiated Resume Propagation and Adjacent Port Side-effects .....                               | 756 |
| Table 4-2 – Upstream Facing Port Receiver Signal/Event Definitions (Addendum) .....                                | 759 |
| Table 4-3 – Upstream Facing Port Transmitter Signal/Event Definitions (Addendum) .....                             | 761 |
| Table 4-4 – Internal Port Signal/Event Definitions (Addendum) .....                                                | 763 |
| Table 4-5 – Downstream Port Signal/Event Definitions (Addendum) .....                                              | 764 |
| Table 4-6 – Summary LPM Timing Characteristics .....                                                               | 767 |
| Table 4-7 – Hub Class Feature Selectors .....                                                                      | 767 |
| Table 4-7 – Hub Class Feature Selectors (cont.) .....                                                              | 768 |
| Table 4-8 – <i>wIndex</i> Definition for Clear Port Feature on an LPM Enabled Hub .....                            | 768 |



|                                                      |     |
|------------------------------------------------------|-----|
| Table 4-9 – Port Status Bits with L1 Additions.....  | 769 |
| Table 4-10 – Port Change Bits with L1 Additions..... | 770 |
| Table 4-11 – Set and Test Port Feature Details ..... | 771 |
| Table 9-7 – Test Mode Selectors .....                | 787 |
| Table 9-7 – Test Mode Selectors .....                | 787 |

**NOTE** All Engineering Change Notices (ECN) and Errata documents as of September 01, 2012 that pertain to this core specification follow the last page of the specification starting on page 635.

## **Universal Serial Bus Specification**

**Compaq  
Hewlett-Packard  
Intel  
Lucent  
Microsoft  
NEC  
Philips**

**Revision 2.0  
April 27, 2000**

### **Scope of this Revision**

The 2.0 revision of the specification is intended for product design. Every attempt has been made to ensure a consistent and implementable specification. Implementations should ensure compliance with this revision.

### **Revision History**

| <b>Revision</b>     | <b>Issue Date</b>  | <b>Comments</b>                                                  |
|---------------------|--------------------|------------------------------------------------------------------|
| 0.7                 | November 11, 1994  | Supersedes 0.6e.                                                 |
| 0.8                 | December 30, 1994  | Revisions to Chapters 3-8, 10, and 11.<br>Added appendixes.      |
| 0.9                 | April 13, 1995     | Revisions to all the chapters.                                   |
| 0.99                | August 25, 1995    | Revisions to all the chapters.                                   |
| 1.0 FDR             | November 13, 1995  | Revisions to Chapters 1, 2, 5-11.                                |
| 1.0                 | January 15, 1996   | Edits to Chapters 5, 6, 7, 8, 9, 10, and 11<br>for consistency.. |
| 1.1                 | September 23, 1998 | Updates to all chapters to fix problems<br>identified.           |
| 2.0 (draft<br>0.79) | October 5, 1999    | Revisions to chapters 5, 7, 8, 9, 11 to add<br>high speed.       |
| 2.0 (draft<br>0.9)  | December 21, 1999  | Revisions to all chapters to add high speed.                     |
| 2.0                 | April 27, 2000     | Revisions for high-speed mode.                                   |

**Universal Serial Bus Specification  
Copyright © 2000, Compaq Computer Corporation,  
Hewlett-Packard Company,  
Intel Corporation,  
Lucent Technologies Inc,  
Microsoft Corporation,  
NEC Corporation,  
Koninklijke Philips Electronics N.V.  
All rights reserved.**

## INTELLECTUAL PROPERTY DISCLAIMER

THIS SPECIFICATION IS PROVIDED TO YOU “AS IS” WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE AUTHORS OF THIS SPECIFICATION DISCLAIM ALL LIABILITY, INCLUDING LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO USE OR IMPLEMENTATION OF INFORMATION IN THIS SPECIFICATION. THE PROVISION OF THIS SPECIFICATION TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS.

All product names are trademarks, registered trademarks, or servicemarks of their respective owners.

Please send comments via electronic mail to [techsup@usb.org](mailto:techsup@usb.org)

For industry information, refer to the USB Implementers Forum web page at <http://www.usb.org>

### Acknowledgement of USB 2.0 Technical Contribution

The authors of this specification would like to recognize the following people who participated in the USB 2.0 Promoter Group technical working groups. We would also like to thank others in the USB 2.0 Promoter companies and throughout the industry who contributed to the development of this specification.

#### Hub Working Group

|                 |                                  |
|-----------------|----------------------------------|
| John Garney     | Intel Corporation (Chair/Editor) |
| Ken Stufflebeam | Compaq Computer Corporation      |
| David Wooten    | Compaq Computer Corporation      |
| Matt Nieberger  | Hewlett-Packard Company          |
| John Howard     | Intel Corporation                |
| Venkat Iyer     | Intel Corporation                |
| Steve McGowan   | Intel Corporation                |
| Geert Knapen    | Royal Philips Electronics        |
| Zong Liang Wu   | Royal Philips Electronics        |
| Jim Clee        | Lucent Technologies Inc          |
| Jim Guziak      | Lucent Technologies Inc          |
| Dave Thompson   | Lucent Technologies Inc          |
| John Fuller     | Microsoft Corporation            |
| Nathan Sherman  | Microsoft Corporation            |
| Mark Williams   | Microsoft Corporation            |
| Nobuo Furuya    | NEC Corporation                  |
| Toshimi Sakurai | NEC Corporation                  |
| Moto Sato       | NEC Corporation                  |
| Katsuya Suzuki  | NEC Corporation                  |

**Electrical Working Group**

|                   |                                  |
|-------------------|----------------------------------|
| Jon Lueker        | Intel Corporation (Chair/Editor) |
| David Wooten      | Compaq Computer Corporation      |
| Matt Nieberger    | Hewlett-Packard Company          |
| Larry Taugher     | Hewlett-Packard Company          |
| Venkat Iyer       | Intel Corporation                |
| Steve McGowan     | Intel Corporation                |
| Mike Pennell      | Intel Corporation                |
| Todd West         | Intel Corporation                |
| Gerrit den Besten | Royal Philips Electronics        |
| Marq Kole         | Royal Philips Electronics        |
| Zong Liang Wu     | Royal Philips Electronics        |
| Jim Clee          | Lucent Technologies Inc          |
| Jim Guziak        | Lucent Technologies Inc          |
| Par Parikh        | Lucent Technologies Inc          |
| Dave Thompson     | Lucent Technologies Inc          |
| Ed Giaimo         | Microsoft Corporation            |
| Mark Williams     | Microsoft Corporation            |
| Toshihiko Ohtani  | NEC Corporation                  |
| Kugao Ouchi       | NEC Corporation                  |
| Katsuya Suzuki    | NEC Corporation                  |
| Toshio Tasaki     | NEC Corporation                  |

## **UNIVERSAL SERIAL BUS INTERFACES FOR DATA AND POWER –**

### **Part 2-1: Universal Serial Bus Specification, Revision 2.0**

## **1 Chapter 1 Introduction**

### **1.1 Motivation**

The original motivation for the Universal Serial Bus (USB) came from three interrelated considerations:

- Connection of the PC to the telephone

It is well understood that the merge of computing and communication will be the basis for the next generation of productivity applications. The movement of machine-oriented and human-oriented data types from one location or environment to another depends on ubiquitous and cheap connectivity. Unfortunately, the computing and communication industries have evolved independently. The USB provides a ubiquitous link that can be used across a wide range of PC-to-telephone interconnects.

- Ease-of-use

The lack of flexibility in reconfiguring the PC has been acknowledged as the Achilles' heel to its further deployment. The combination of user-friendly graphical interfaces and the hardware and software mechanisms associated with new-generation bus architectures have made computers less confrontational and easier to reconfigure. However, from the end user's point of view, the PC's I/O interfaces, such as serial/parallel ports, keyboard/mouse/joystick interfaces, etc., do not have the attributes of plug-and-play.

- Port expansion

The addition of external peripherals continues to be constrained by port availability. The lack of a bi-directional, low-cost, low-to-mid speed peripheral bus has held back the creative proliferation of peripherals such as telephone/fax/modem adapters, answering machines, scanners, PDA's, keyboards, mice, etc. Existing interconnects are optimized for one or two point products. As each new function or capability is added to the PC, a new interface has been defined to address this need.

The more recent motivation for USB 2.0 stems from the fact that PCs have increasingly higher performance and are capable of processing vast amounts of data. At the same time, PC peripherals have added more performance and functionality. User applications such as digital imaging demand a high performance connection between the PC and these increasingly sophisticated peripherals. USB 2.0 addresses this need by adding a third transfer rate of 480 Mb/s to the 12 Mb/s and 1.5 Mb/s originally defined for USB. USB 2.0 is a natural evolution of USB, delivering the desired bandwidth increase while preserving the original motivations for USB and maintaining full compatibility with existing peripherals.

Thus, USB continues to be the answer to connectivity for the PC architecture. It is a fast, bi-directional, isochronous, low-cost, dynamically attachable serial interface that is consistent with the requirements of the PC platform of today and tomorrow.

### **1.2 Objective of the Specification**

This document defines an industry-standard USB. The specification describes the bus attributes, the protocol definition, types of transactions, bus management, and the

programming interface required to design and build systems and peripherals that are compliant with this standard.

The goal is to enable such devices from different vendors to interoperate in an open architecture. The specification is intended as an enhancement to the PC architecture, spanning portable, business desktop, and home environments. It is intended that the specification allow system OEMs and peripheral developers adequate room for product versatility and market differentiation without the burden of carrying obsolete interfaces or losing compatibility.

### **1.3 Scope of the Document**

The specification is primarily targeted to peripheral developers and system OEMs, but provides valuable information for platform operating system/ BIOS/ device driver, adapter IHVs/ISVs, and platform/adaptor controller vendors. This specification can be used for developing new products and associated software.