

INTERNATIONAL STANDARD

**High frequency inductive components - Electrical characteristics and measuring methods -
Part 3: AC loss measured by sinusoidal wave of inductors for DC-to-DC converters**

CONTENTS

FOREWORD	2
INTRODUCTION	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Select measuring method	5
5 Cross-power method	5
5.1 General	5
5.2 Measuring method	6
5.2.1 Measuring circuit	6
5.2.2 Measuring jig	6
5.2.3 Practical notes	7
6 Amplified vector network analyzer method	8
6.1 General	8
6.2 Measuring method	8
6.2.1 Measuring method overview	8
6.2.2 Measuring circuit	8
6.2.3 Measuring jig	10
6.2.4 Calibration	11
6.2.5 Calculation method	12
6.2.6 Practical notes	14
Annex A (informative) Measuring accuracy	15
A.1 Method for confirming measuring accuracy	15
A.2 Case studies of AC loss measurements in different waveforms	15
A.3 Measuring error due to bias T	16
A.3.1 General	16
A.3.2 Cross-power method	16
A.3.3 Amplified vector network analyzer method	16
Bibliography	17
Figure 1 – Example of measuring circuit of cross-power method	6
Figure 2 – Example of measuring jig of cross-power method	7
Figure 3 – Measuring circuit of amplified vector network analyzer method	8
Figure 4 – Measuring circuit of amplified vector network analyzer method	10
Figure 5 – Measuring jig of amplified vector network analyzer method	11
Figure 6 – Compensation jig of amplified vector network analyzer method	12
Figure A.1 – AC loss difference with triangular wave (duty 50 %, frequency 10 kHz)	16
Table 1 – AC loss measuring method	5

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**High frequency inductive components -
Electrical characteristics and measuring methods -
Part 3: AC loss measured by sinusoidal wave of
inductors for DC-to-DC converters**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62024-3 has been prepared by IEC technical committee 51: Magnetic components, ferrite and magnetic powder materials. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
51/1617/FDIS	51/1625/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 62024 series, published under the general title *High frequency inductive components - Electrical characteristics and measuring methods*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INTRODUCTION

This document is intended for high-frequency inductive components used in DC-to-DC converters.

Power saving of DC-to-DC converters is crucial owing to heat generation measures for miniaturization and high-density mounting, longer battery life for mobile devices, and increased power consumption in data centres with increased communication traffic. Under these circumstances, the loss of high-frequency inductive components is an important characteristic that determines the power saving of DC-to-DC converters. To measure the loss for possible implementation in DC-to-DC converters, it is important to measure the AC loss at current values close to the actual drive, but there was no measurement standard. AC loss measurements for high-frequency inductive components are defined in IEC 62024-1, but the measured currents are small and are not intended to be driven by DC-to-DC converters. IEC 62044-3 and IEC 63300 address testing for large alternating current, but the applications are different because they are for magnetic materials such as cores. Therefore, appropriate metrics for high-frequency inductive components for DC-to-DC converter are crucial. This document introduces a method for measuring the loss of high frequency inductive components when an alternating current corresponding to the actual drive is applied.

This document is one of the IEC 62024 series of standards for high-frequency inductive parts.

This document specifies the test method and a measuring jig for accurately comparing AC losses of high-frequency inductive components for DC-to-DC converters by sinusoidal wave current. This document also presents measuring principles, application ranges, and attentions of each method. Two different measurement methods with different ranges of measurement frequencies are presented. AC losses are measured by setting the frequency, the magnitude of the current, and the DC bias current.

The inductor current used in a DC-to-DC converter is a triangular wave, and the inductor loss depends on the shape of the triangular wave in addition to the current, frequency, and DC bias current. Therefore, the loss value measured by the measurement method using the sinusoidal current in this document does not necessarily match the inductor loss of the DC-to-DC converter, even if the same effective current is used. The measurement results are described in Annex A.

In the future, a separate standard defining the triangular current drive testing can be developed for publication.

1 Scope

This part of IEC 62024 specifies test methods for AC losses of high-frequency inductive components for power supplies used in DC-to-DC converters and similar devices at currents close to actual operation and introduces the measurement principle, scope of application and matters to be noted for each method. This document is applicable to leaded and surface mount inductors with dimensions in accordance with IEC 62024-2.

2 Normative references

There are no normative references in this document.

Bibliography

IEC 62024-1, *High frequency inductive components - Electrical characteristics and measuring methods - Part 1: Nanohenry range chip inductor*

IEC 62024-2, *High frequency inductive components - Electrical characteristics and measuring methods - Part 2: Rated current of inductors for DC-to-DC converters*

IEC 62044-3, *Cores made of soft magnetic materials - Measuring methods - Part 3: Magnetic properties at high excitation level*

IEC 63300, *Test methods for electrical and magnetic properties of magnetic powder cores*
