

INTERNATIONAL STANDARD

REDLINE VERSION

**High-frequency dielectric heating installations - Test methods for the
determination of power output**

CONTENTS

FOREWORD	2
1 Scope and object	4
2 Normative references	5
3 Terms and definitions	5
4 Test loads	6
4.1 General	6
4.2 Calorimeter Calorimetric load	6
4.3 Lamp load	6
4.4 Matched resistive load	7
4.5 Wet-sand load	7
5 Description of tests	7
5.1 General	7
5.2 Calorimeter Calorimetric load method	7
5.3 Lamp-load temperature method	10
5.4 Matched resistive load method	12
5.5 Wet-sand load method	12
5.6 Evaluation of the output power for high-frequency dielectric plastic welders	13
5.6.1 General	13
5.6.2 Test with plastic material	13
5.7 Evaluation of the output power for type B equipment	14
Annex A (informative) Recommended test circuit for the lamp-load method	15
Figure 1 – Example of a calorimeter load	9
Figure 2 – Example of a short tubular calorimeter load	10
Figure 3 – Lamp-load circuit	10
Figure 4 – Example of a lamp load	11
Figure 5 – Detail of the lamp load	12
Figure 6 – Plastic welding test electrode	14
Figure A.1 – Recommended test circuit for the lamp-load method	15

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**High-frequency dielectric heating installations -
Test methods for the determination of power output**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 61308:2005. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

IEC 61308 has been prepared by IEC technical committee 27: Industrial electroheating and electromagnetic processing. It is an International Standard.

This third edition cancels and replaces the second edition published in 2005. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) adaptation and alignment to the principles in more recent editions of IEC 60519-1 and IEC 60519-6;
- b) more detailed descriptions of, in particular, the calorimetric load test and output power evaluation for dielectric plastic welders.

The text of this International Standard is based on the following documents:

Draft	Report on voting
27/1244/FDIS	27/1248/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

1 ~~Scope and object~~

~~This International Standard is applicable to industrial high frequency dielectric heating installations used for the purpose of thermal applications such as melting, drying, welding, insect extermination, and gluing of partially conductive or non-conductive materials such as plastics, wood, rubber, textiles, glass, ceramic, paper, bamboo or foodstuffs, in both normal and protective atmospheres, using, for example, inert gases or vacuum.~~

~~This standard relates to high frequency dielectric heating installations with nominal dielectric heating frequency in the range from 1 MHz to 300 MHz with rated useful output power greater than 50 W.~~

~~The main purpose of this standard is to assist in compliance with the requirements set out in 6.4 of IEC 60519-9 when testing electroheating power sources. It is not primarily intended as a means of representing a potential high frequency heating application for the requirement of the user. Due to the large variety of dielectric heating applications, any output power value obtained as a result of these tests should not always be taken as representing the power that can be dissipated in a particular dielectric heating installation, but, in certain instances, the output power value could be used as an indication of performance.~~

~~The power required to heat a charge is dependent, for example, on the type of material heated, the temperature of heating and ambient moisture and on the construction of the electrode system.~~

~~NOTE Heating a charge with dielectric parameters deeply changing in time and/or temperature the value of the output power obtained with the actual charge may be different from that obtained in standard test conditions.~~

~~For equipment working outside the ITU-designated bands, the frequency of the generator follows the resonant frequency of the output circuit, thus the output power can remain fairly stable during the work cycle, even with hand tuning of the output circuit. Therefore, according to this standard, the test well represents the actual output power in practical work conditions.~~

~~For equipment working in ITU-designated bands, the frequency of the generator remains stable, but the resonant frequency of the output circuit varies with the change of dielectric parameters of the load. Therefore, the value of the mean output power in the work cycle can be much lower than the value obtained in the test conditions. This value depends on the time response of the eventual automatic tuning system.~~

This document specifies test methods for the determination of useful high frequency power output in equipment for industrial heating and processing of materials. It is in particular applicable to HF generators made available to users as separate units.

This document is basically applicable to equipment operating in the frequency range 100 kHz to 300 MHz, as defined in IEC 60519-1, with the following limitations.

- This document does not apply to induction heating, which it is possible to carry out in the lower part of the specified frequency band.
- The ISM centre frequencies for dielectric heating and processing of industrial interest are narrow bands about 6,78 MHz, 13,56 MHz, 27,12 MHz and 40,68 MHz.
- This document is not applicable to:
 - appliances for household and similar use;
 - commercial use;
 - laboratory use;
 - medical high frequency equipment.

For equipment working in designated ISM bands, it is a legal requirement that the frequency remains within the ISM bands according to CISPR 11, but the resonant frequency of the circuit varies with the change of dielectric parameters of the load. Therefore, the value of the mean output power in the work cycle can be much lower than the value obtained under the test conditions. This value depends upon the response of the tuning system.

NOTE 1 The following criteria are suitable for determination of the classification as industrial equipment:

- commercial equipment is typically designed and planned for series production of many identical units;
- industrial equipment is typically produced in small series or even as single units; the processed goods are consumed or ready for final use at the end of the heating process.

NOTE 2 Heating a workload with dielectric parameters which change significantly in time and/or with temperature, the value of the output power obtained with the actual charge can be different from that obtained with the test load specified in this document.

This document relates to equipment normally operating under continuous rated conditions.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-841:~~2004~~, *International Electrotechnical Vocabulary (IEV) - Part 841: Industrial electroheat*

IEC 60519-1, *Safety in installations for electroheating and electromagnetic processing - Part 1: General requirements*

IEC 60519-6, *Safety in installations for electroheating and electromagnetic processing - Part 6: Particular requirements for high frequency dielectric and microwave heating and processing equipment*

~~IEC 60519-9, Safety in electroheat installations — Part 9: Particular requirements for high-frequency dielectric heating installations~~