

INTERNATIONAL STANDARD

**Plugs, socket-outlets, vehicle connectors and vehicle inlets - Conductive charging of electric vehicles -
Part 3: Dimensional compatibility requirements for DC and AC/DC pin and contact-tube vehicle couplers**

CONTENTS

FOREWORD	7
INTRODUCTION	9
1 Scope	10
2 Normative references	10
3 Terms and definitions	11
4 General	11
4.1 General requirements	11
5 Ratings	12
6 Connection between the power supply and the electric vehicle	12
7 Classification of accessories	15
8 Marking	15
9 Dimensions	16
10 Protection against electric shock	16
11 Size and colour of protective earthing and neutral conductors	17
12 Provisions for earthing	18
13 Terminals	18
14 Interlocks	18
14.301 Latching function	18
14.302 Engage and disengage the latching device (configuration FF)	19
14.302.1 General	19
14.302.2 Samples	19
14.302.3 Test sequence	19
14.302.4 Test gauge	21
15 Resistance to ageing of rubber and thermoplastic material	24
16 General construction	25
17 Construction of EV socket-outlets	25
18 Construction of EV plugs and vehicle connectors	25
19 Construction of vehicle inlets	26
20 Degrees of protection	26
21 Insulation resistance and dielectric strength	26
22 Breaking capacity	26
23 Normal operation	26
24 Temperature rise	26
25 Flexible cables and their connection	27
26 Mechanical strength	28
27 Screws, current-carrying parts and connections	28
28 Creepage distances, clearances and distances through sealing compound	28
29 Resistance to heat and to fire	28
30 Corrosion and resistance to rusting	28
31 Conditional short-circuit current	28
32 Electromagnetic compatibility	28
33 Vehicle drive over	29
34 Thermal cycling	29

35	Humidity exposure	29
36	Misalignment	29
37	Contact endurance test.....	29
	STANDARD SHEETS CONFIGURATION AA	30
	STANDARD SHEETS CONFIGURATION BB	39
	STANDARD SHEETS CONFIGURATION EE	43
	STANDARD SHEETS CONFIGURATION FF.....	60
	Annex A (normative) Standard sheets for test gauges in 14.1.9	82
	Annex B (informative) EV accessories directly connected to printed circuit boards (PCBs).....	83
	Annex AA (normative) Vehicle connector, vehicle inlet and cable assembly for DC charging intended to be used with a thermal management system	84
	AA.1 General.....	84
	AA.2 Normative references.....	84
	AA.3 Terms and definitions.....	84
	AA.4 General.....	84
	AA.4.301 System architecture	90
	AA.4.302 Manufacturers data sheet	92
	AA.5 Ratings	92
	AA.6 Connection between the power supply and the electric vehicle	92
	AA.7 Classification of accessories	93
	AA.8 Marking.....	93
	AA.9 Dimensions	93
	AA.10 Protection against electric shock.....	93
	AA.11 Size and colour of protective earthing and neutral conductors.....	93
	AA.12 Provision for earthing	93
	AA.13 Terminals.....	93
	AA.14 Interlocks	93
	AA.15 Resistance to ageing of rubber and thermoplastic material	94
	AA.16 General construction.....	94
	AA.16.100 Thermal sensing device	94
	AA.16.101 Loss of thermal transport	94
	AA.16.102 Accessories using thermal sensing	95
	AA.16.103 Rated current for accessory	95
	AA.16.104 Operation conditions of thermal management system	95
	AA.16.105 Minimum cross section of line conductors	96
	AA.16.106 Contact temperature	96
	AA.17 Construction of EV socket-outlets	96
	AA.18 Construction of EV plugs and vehicle connectors	96
	AA.19 Construction of vehicle inlets	96
	AA.20 Degrees of protection.....	96
	AA.21 Insulation resistance and dielectric strength.....	96
	AA.22 Breaking capacity	96
	AA.23 Normal operation	96
	AA.24 Temperature rise	97
	AA.24.1 General conditions.....	97
	AA.24.2 Temperature rise test for cable assembly	97
	AA.24.3 Test for thermal sensing device of cable assembly	98

AA.24.4	Test for thermal sensing device of configuration GG cable assembly	99
AA.24.5	Temperature rise test for vehicle inlet	102
AA.24.6	Test for thermal sensing device of vehicle inlet	103
AA.24.7	Temperature rise test for cable assembly with thermal transport off	104
AA.25	Flexible cables and their connection	104
AA.26	Mechanical strength	105
AA.27	Screws, current-carrying parts and connections	106
AA.28	Creepage distances, clearances and distances through sealing compound	106
AA.29	Resistance to heat and to fire	106
AA.30	Corrosion and resistance to rusting	106
AA.31	Conditional short-circuit current	106
AA.32	Electromagnetic compatibility	106
AA.33	Vehicle drive over	107
AA.34	Thermal cycling	107
AA.35	Humidity exposure	107
AA.36	Misalignment	107
AA.37	Contact endurance test	107
AA.38	Liquid coolants	107
AA.38.1	Type of coolant	107
AA.38.2	Environmental considerations	107
AA.38.3	Flammability	108
AA.38.4	Conductivity	108
AA.38.5	Material compatibility	108
AA.38.6	Overpressure test	109
AA.39	Specific information for configuration AA	109
AA.39.1	General	109
AA.39.2	Reference devices and test setups for configuration AA	109
AA.39.3	Test setup for configuration AA	116
AA.39.4	Contacts for configuration AA	117
AA.40	Specific information for configuration BB	118
AA.41	Specific information for configuration EE	118
AA.41.1	General	118
AA.41.2	Reference devices and test setups for configuration EE	118
AA.41.3	Test setup for configuration EE	124
AA.41.4	Contacts for configuration EE	125
AA.42	Specific information for configuration FF	126
AA.42.1	General	126
AA.42.2	Reference devices and test setups for configuration FF	126
AA.42.3	Test setup for configuration FF	133
AA.42.4	Contacts for configuration FF	134
AA.43	Specific information for configuration GG	134
AA.43.1	General	134
AA.43.2	Reference devices and test setups for configuration GG	135
AA.43.3	Test setup for configuration GG	141
AA.43.4	Contacts for configuration GG	142
AA.44	Recommended data	142
AA.44.1	General	142
AA.44.2	List of recommended data	142

Annex BB (informative) Coordinate systems and package spaces for automatic docking and undocking of vehicle connectors and vehicle inlets.....	144
BB.1 General.....	144
BB.2 Configuration FF	144
BB.2.1 Coordinate system of vehicle inlet	144
BB.2.2 Coordinate system of vehicle connector.....	144
BB.2.3 Package space for automatic docking.....	144
Annex CC (informative) Recommended AC/DC arrangement for configuration GG.....	145
Bibliography.....	146

Figure 301 – Example of test setup for checking latched position and unlatched position.....	20
Figure 302 – Test gauge vehicle connector (configuration FF) – Side view	21
Figure 303 – Test gauge of vehicle connector (configuration FF) – Detail 1	22
Figure 304 – Test gauge of vehicle connector (configuration FF) – Detail 2	22
Figure 305 – Test gauge of vehicle connector (configuration FF) – Detail 3	23
Figure 306 – Test gauge of vehicle connector (configuration FF) – Detail 4	23
Figure 307 – Test gauge of vehicle connector (configuration FF) – Detail 5	24
Figure 308 – Test gauge of vehicle connector (configuration FF) – Detail 6	24
Figure AA.100 – DC EV supply equipment with thermal sensing	91
Figure AA.101 – DC EV supply equipment with thermal sensing, thermal transport and thermal exchange	92
Figure AA.102 – Reference device (configuration AA).....	110
Figure AA.103 – Test setup (configuration AA) for temperature rise test of cable assembly	111
Figure AA.104 – Test setup (configuration AA) for temperature rise test of vehicle inlet (test step 1 of AA.24.5).....	112
Figure AA.105 – Test setup (configuration AA) for temperature rise test of vehicle inlet (test step 2 of AA.24.5).....	113
Figure AA.106 – Reference device with heating unit (configuration AA) for thermal sensing test of cable assembly	113
Figure AA.107 – Test setup with heating unit (configuration AA) for thermal sensing test of cable assembly	114
Figure AA.108 – Reference device with heating unit (configuration AA) for thermal sensing test of vehicle inlet.....	115
Figure AA.109 – Test setup with heating unit (configuration AA) for thermal sensing test of vehicle inlet.....	116
Figure AA.110 – General test setup for temperature rise tests and thermal sensing device tests (configuration AA)	116
Figure AA.111 – Plating of contacts for configuration AA	117
Figure AA.112 – Reference device (configuration EE).....	119
Figure AA.113 – Test setup (configuration EE) for temperature rise test of cable assembly	120
Figure AA.114 – Test setup (configuration EE) for temperature rise test of vehicle inlet (test step 1 of AA.24.5).....	120
Figure AA.115 – Test setup (configuration EE) for temperature rise test of vehicle inlet (test step 2 of AA.24.5).....	121

Figure AA.116 – Reference device with heating unit (configuration EE) for thermal sensing test of cable assembly	122
Figure AA.117 – Test setup with heating unit (configuration EE) for thermal sensing test of cable assembly	122
Figure AA.118 – Reference device with heating unit (configuration EE) for thermal sensing test of vehicle inlet.....	123
Figure AA.119 – Test setup with heating unit (configuration EE) for thermal sensing test of vehicle inlet.....	123
Figure AA.120 – General test setup for temperature rise tests and thermal sensing device tests (configuration EE)	124
Figure AA.121 – Plating of contacts for configuration EE	125
Figure AA.122 – Reference device (configuration FF)	127
Figure AA.123 – Test setup (configuration FF) for temperature rise test of cable assembly	128
Figure AA.124 – Test setup (configuration FF) for temperature rise test of vehicle inlet (test step 1 of AA.24.5)	129
Figure AA.125 – Test setup (Configuration FF) for temperature rise test of vehicle inlet (test step 2 of AA.24.5)	130
Figure AA.126 – Reference device with heating unit (configuration FF) for thermal sensing test of cable assembly	131
Figure AA.127 – Test setup with heating unit (configuration FF) for thermal sensing test of cable assembly	132
Figure AA.128 – Reference device with heating unit (configuration FF) for thermal sensing test of vehicle inlet.....	132
Figure AA.129 – Test setup with heating unit (configuration FF) for thermal sensing test of vehicle inlet.....	133
Figure AA.130 – General test setup for temperature rise tests and thermal sensing device tests (configuration FF).....	133
Figure AA.131 – Plating of contacts for configuration FF	134
Figure AA.132 – Reference device (configuration GG)	135
Figure AA.133 – Test setup (configuration GG) for temperature rise test of cable assembly	136
Figure AA.134 – Test setup (configuration GG) for temperature rise test of vehicle inlet (test step 1 of AA.24.5)	137
Figure AA.135 – Test setup (configuration GG) for temperature rise test of vehicle inlet (test step 2 of AA.24.5)	137
Figure AA.136 – Reference device with heating unit (configuration GG) for thermal sensing test of cable assembly	138
Figure AA.137– Test setup with heating unit (configuration GG) for thermal sensing test of cable assembly	139
Figure AA.138 – Reference device with heating unit (configuration GG) for thermal sensing test of vehicle inlet.....	140
Figure AA.139 – Test setup with heating unit (configuration GG) for thermal sensing test of vehicle inlet.....	140
Figure AA.140 – General test setup for temperature rise tests and thermal sensing device tests (configuration GG).....	141
Figure AA.141 – Plating of contacts for configuration GG.....	142
Figure CC.100 – Recommended AC/DC arrangement for configuration GG	145

Table 301 – Overview of the DC vehicle interface	13
Table 302 – Overview of the combined AC/DC vehicle interface	14
Table 303 – Interface overview	16
Table 304 – Definition of interlock test numbers for checking latched position and unlatched position.....	19
Table 305 – Properties of contact plating for DC contact pins	25
Table 20 – Pulling force on insulated end caps	28
Table 306 – Functionality of the contacts for configuration EE	43
Table 307 – Functionality of the contacts for DC configuration FF.....	60
Table 1 – Overview of applicable tests for different classifications of accessories	85
Table 2 – Test sequence A	89
Table 3 – Test sequence B	89
Table 4 – Test sequence C	90
Table 5 – Test sequence D	90
Table 15 – Pull force and torque test values for cable anchorage.....	105
Table 17 – Impact energy for ball impact test.....	105
Table AA.107 – Maximum contact resistances and dimensions of reference device in Figure AA.102.....	110
Table AA.108 – Dimensions for reference device conductor (configuration AA).....	117
Table AA.109 – Contact resistances and dimensions of reference device in Figure AA.112.....	119
Table AA.110 – Dimensions for reference device conductor (configuration EE).....	124
Table AA.111 – Contact resistances and dimensions of reference device in Figure AA.122.....	127
Table AA.112 – Dimensions for reference device conductor (configuration FF)	134
Table AA.113 – Maximum contact resistances and dimensions of reference device in Figure AA.132.....	136
Table AA.114 – Dimensions for reference device conductor (configuration GG)	141

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**Plugs, socket-outlets, vehicle connectors and vehicle inlets -
Conductive charging of electric vehicles -
Part 3: Dimensional compatibility requirements
for DC and AC/DC pin and contact-tube vehicle couplers**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62196-3 has been prepared by IEC subcommittee 23H: Plugs, socket-outlets, and couplers for industrial and similar applications, and for electric vehicles, of IEC technical committee 23: Electrical accessories. It is an International Standard.

This third edition cancels and replaces the second edition published in 2022. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) The content of IEC TS 62196-3-1 has been integrated into this document as normative Annex AA.
- b) increased ratings for all configurations;

c) reference to new tests in IEC 62196-1:2025 (Clauses 34, 35, 36 and 37).

The text of this International Standard is based on the following documents:

Draft	Report on voting
23H/588/FDIS	23H/595/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

This document is to be read in conjunction with IEC 62196-1:2025. The clauses of the particular requirements in this document supplement or modify the corresponding clauses in IEC 62196-1:2025. Where the text indicates an "addition" to or a "replacement" of the relevant requirement, test specification or explanation of IEC 62196-1:2025, these changes are made to the relevant text of IEC 62196-1:2025, which then becomes part of this document. Where no change is necessary, the words "IEC 62196-1:2025, Clause X, applies" are used. Additional annexes are numbered Annex AA, Annex BB, etc. Subclauses, figures, tables, or notes which are additional to those in IEC 62196-1:2025 are numbered starting from 301.

Annex AA follows the numbering of IEC 62196-1:2025 and of this document. Additional figures and tables to this document in Annex AA are numbered starting from AA.100.

In this document, the following print types are used:

- requirements proper: in roman type;
- *test specifications: in italic type;*
- notes: in smaller roman type.

A list of all the parts in the IEC 62196 series, published under the general title *Plugs, socket-outlets, vehicle connectors and vehicle inlets - Conductive charging of electric vehicles*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

The content of the corrigendum 1 (2026-08) has been included in this copy.

INTRODUCTION

The IEC 61851 series specifies requirements for electric vehicle (EV) conductive supply equipment.

The IEC 62196 series specifies the requirements for plugs, socket-outlets, vehicle connectors, vehicle inlets and cable assemblies as described in the IEC 61851 series and in IEC 62752.

Charging using off-board DC charging equipment can be achieved by the direct connection of an electric vehicle to DC EV supply equipment incorporating control and communication circuits.

To support the connection of DC power for such vehicles, this document provides the standard interface configurations of DC vehicle couplers and accessories to be used in conductive charging of electric vehicles, taking the most frequent charging situations into consideration.

The IEC 62196 series consists of the following parts:

- IEC 62196-1: General requirements, comprising clauses of a general character;
- IEC 62196-2: Dimensional compatibility requirements for AC pin and contact-tube accessories;
- IEC 62196-3: Dimensional compatibility requirements for DC and AC/DC pin and contact-tube vehicle couplers;
- IEC TS 62196-4: Dimensional compatibility and interchangeability requirements for DC pin and contact-tube accessories for class II or class III applications;
- IEC 62196-6: Dimensional compatibility requirements for DC pin and contact-tube vehicle couplers intended to be used for DC EV supply equipment where protection relies on electrical separation.
- IEC TS 62196-7: Vehicle adapter

1 Scope

This part of IEC 62196 is applicable to vehicle couplers with pins and contact tubes of standardized configuration, herein also referred to as "accessories", intended for use in electric vehicle conductive charging systems which incorporate control means, with rated operating voltage and current in accordance with IEC 62196-1:2025.

This document applies to high power DC interfaces and combined AC/DC interfaces of vehicle couplers that are intended for use in conductive charging systems for circuits specified in IEC 61851-1 and IEC 61851-23.

This document applies to accessories and cable assemblies that employ

- thermal sensing, or
- thermal transport and thermal sensing with the system architecture described in AA.4.301.

The DC vehicle connectors and vehicle inlets covered by this document are used only in charging mode 4, case C, as shown in IEC 61851-1.

These vehicle couplers are intended to be used for circuits specified in IEC 61851-23 which operate at different voltages, and which can include ELV and communication signals.

This document applies to the vehicle couplers to be used in an ambient temperature between $-30\text{ }^{\circ}\text{C}$ and $+40\text{ }^{\circ}\text{C}$.

NOTE 1 In some countries, other requirements can apply.

NOTE 2 In the following country, $-40\text{ }^{\circ}\text{C}$ applies: SE.

These vehicle couplers are intended to be connected only to cables with copper or copper-alloy conductors.

These accessories are intended to be connected to cables according to the IEC 62893 series for DC cables.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60364-5-54:2011, *Low-voltage electrical installations - Part 5-54: Selection and erection of electrical equipment - Earthing arrangements and protective conductors*

IEC 60811-501, *Electric and optical fibre cables - Test methods for non-metallic materials - Part 501: Mechanical tests - Tests for determining the mechanical properties of insulating and sheathing compounds*

IEC 61851-23:2023, *Electric vehicle conductive charging system - part 23: DC electric vehicle supply equipment*

IEC 62196-1:2025, *Plugs, socket-outlets, vehicle connectors and vehicle inlets - Conductive charging of electric vehicles - Part 1: General requirements*

IEC 62196-2:2025, *Plugs, socket-outlets, vehicle connectors and vehicle inlets - Conductive charging of electric vehicles - Part 2: Dimensional compatibility requirements for AC pin and contact-tube accessories*

IEC 62893-4-1, *Charging cables for electric vehicles of rated voltages up to and including 0,6/1 kV - Part 4-1: Cables for DC charging according to mode 4 of IEC 61851-1 - DC charging without use of a thermal management system*

ISO 2719, *Determination of flash point - Pensky-Martens closed cup method*

ISO 4521, *Metallic and other inorganic coatings - Electrodeposited silver and silver alloy coatings for engineering purposes - Specification and test methods*

ISO 5474-3:2024, *Electrically propelled road vehicles - Functional and safety requirements for power transfer between vehicle and external electric circuit - Part 3: DC power transfer*

ISO 25178-1, *Geometrical product specifications (GPS) - Surface texture: Areal - Part 1: Indication of surface texture*

Globally Harmonized System of Classification and Labelling of Chemicals (GHS), tenth edition, United Nations, 2023

OECD Guidelines for the Testing of Chemicals, Section 3, Test No. 301: Ready Biodegradability, 17 July 1992

Bibliography

IEC 60216-1, *Electrical insulating materials - Thermal endurance properties - Part 1: Ageing procedures and evaluation of test results*

IEC 61851 (all parts), *Electric vehicle conductive charging system*

IEC 61851-1:2017, *Electric vehicle conductive charging system - Part 1: General requirements*

IEC 61851-23, *Electric vehicle conductive charging system - Part 23: DC electric vehicle supply equipment*²

IEC 61851-24, *Electric vehicle conductive charging system - Part 24: Digital communication between a DC EV supply equipment and an electric vehicle for control of DC charging*

IEC TS 61851-26, *Electric vehicle conductive charging system - Part 26: EV supply equipment with automatic docking of a vehicle coupler located at the underbody of an electric vehicle*

IEC TS 61851-27, *Electric vehicle conductive charging system - Part 27: EV supply equipment with automated docking of a vehicle coupler according to IEC 62196-2, IEC 62196-3 or IEC TS 62196-3-1*

IEC TS 62196-3-1, *Plugs, socket-outlets, vehicle connectors and vehicle inlets - Conductive charging of electric vehicles - Part 3-1: Vehicle connector, vehicle inlet and cable assembly for DC charging intended to be used with a thermal management system*

IEC 62893 (all parts), *Charging cables for electric vehicles of rated voltages up to and including 0,6/1 kV*

IEC TS 62893-4-2, *Charging cables for electric vehicles of rated voltages up to and including 0,6/1 kV - Part 4-2: Cables for DC charging according to mode 4 of IEC 61851-1 - Cables intended to be used with a thermal management system*

ISO 2768-1, *General tolerances - Part 1: Tolerances for linear and angular dimensions without individual tolerance indications*

ISO 5474 (all parts), *Electrically propelled road vehicles - Functional and safety requirements for power transfer between vehicle and external electric circuit*

ISO 19642-5:2019, *Road vehicles - Automotive cables - Part 5: Dimensions and requirements for 600 V a.c. or 900 V d.c. and 1 000 V a.c or 1 500 V d.c. single core copper conductor cables*

ISO 20457, *Plastics moulded parts - Tolerances and acceptance conditions*

² Third edition under preparation. Stage at the time of publication: IEC/CD 61851-23:2025.