

INTERNATIONAL STANDARD

**Lead-acid starter batteries -
Part 8: 12V Batteries used in automobiles for auxiliary or backup purposes**

CONTENTS

FOREWORD	4
INTRODUCTION	6
1 Scope	7
2 Normative references	7
3 Terms, definitions, abbreviated terms and symbols	7
3.1 Terms and definitions	7
3.2 Abbreviated terms and symbols	8
4 Categories and designation of batteries for auxiliary or backup applications	9
4.1 Categories	9
4.2 Designation according to type	9
5 Condition on delivery	9
6 General requirements	10
6.1 Identification and labelling	10
6.1.1 General	10
6.1.2 The identification of the manufacturer or supplier	10
6.1.3 Nominal voltage: 12 V	10
6.1.4 Capacity or reserve capacity and nominal high rate current CCA	10
6.1.5 Production date code	10
6.1.6 Safety labelling	10
6.1.7 Recycling labelling	10
6.1.8 Valve-regulated batteries	10
6.2 Marking of the polarity and fastening of the battery	10
7 Functional characteristics	11
7.1 Electrical characteristics	11
7.2 Mechanical characteristics	11
8 General test conditions	12
8.1 Sampling of batteries	12
8.2 Charging method – Definition of a fully charged battery	12
8.3 Test equipment	12
8.3.1 Measuring instruments	12
8.3.2 Water bath	12
8.3.3 Environmental chamber	12
8.4 Test sequence	12
8.4.1 General-use automotive batteries	12
8.4.2 Dedicated auxiliary or backup batteries	13
9 Test methods	14
9.1 20 h capacity check C_e	14
9.2 Reserve capacity check RC_e	14
9.3 Cranking performance test	14
9.3.1 Cranking performance test for auxiliary or backup batteries	14
9.4 Pulse power characterization (PPC)	14
9.4.1 Introduction and purpose	14
9.4.2 Pulse power characterization test – BOL	15
9.4.3 Pulse power characterization test – EOL	16
9.4.4 Pulse profiles	18

9.5	Charge acceptance test at 0 °C	20
9.6	Charge recovery test at -18 °C.....	20
9.7	Endurance test for batteries	23
9.7.1	Corrosion test.....	23
9.7.2	Cycling test 50 % DoD.....	23
9.7.3	Optional endurance cycle test (applicable only to Categories 1C, 2 and 3)	24
9.7.4	Cycling test 17,5 % DoD	25
9.8	Charge retention test	26
9.9	Electrolyte retention test	26
9.10	Vibration resistance test	26
9.11	Water consumption test	26
9.12	High temperature durability test (informative only)	26
10	Requirements	27
10.1	General automotive batteries	27
10.2	Dedicated auxiliary or backup batteries.....	27
10.3	Requirements for PPC test.....	28
10.3.1	Fixed voltage requirements for relative discharge rates (if PP1 is used):	28
10.3.2	Voltage requirements to be calculated for each fixed current pulse (if PP2 is used).....	29
10.4	Requirements for charge recovery test.....	29
10.5	Results reporting format.....	29
Annex A (informative)	Result reporting.....	30
Annex B (informative)	Information on pulse power characterization (PPC)	35
B.1	Rationale and background information	35
B.2	Determination of PPC requirements	38
B.3	Recommendations for power performance mapping	39
B.3.1	General	39
B.3.2	<i>T</i> -loop procedure with SOC preconditioning at nominal conditions	41
B.3.3	SOC-loop procedure with stepwise SOC preconditioning target temperature	44
Annex C (informative)	Information on charge recovery (CR) testing	47
C.1	General.....	47
C.2	Determination of CR requirements	49
C.3	Transfer to other operating conditions.....	49
Figure B.1	– Typical pulse-power mapping results for one EFB type by SOC-loop procedure at variable temperature, SOC, and ageing condition.....	36
Figure B.2	– Example reporting format for PPC results for one AGM battery type by <i>T</i> -loop procedure.....	37
Figure B.3	– Three-dimensional representation of test data from Figure B.2, pulse 1: peak discharge current that can be delivered for 5 s above 9,2 volts at battery terminals.....	38
Figure B.4	– PPC mapping results and requirement setting.....	39
Figure C.1	– Recommended diagram styles for CR reporting and analysis.....	48
Figure C.2	– Test data and requirements (dotted red line) for SOC and SOF recovery in the CR test.....	48
Figure C.3	– Absolute U_{10s} results for SOF recovery in the CR test	49
Figure C.4	– Variants of preconditioning to 50 % SOC during CR test development	51

Figure C.5 – Correlation of "CR-weekend -18 °C" results with other CR test results.....	52
Table 1 – Charging method.....	12
Table 2 – Test sequence.....	13
Table 3 – PPC at beginning of life (BOL) – Categories 1, 2 and 3	15
Table 4 – PPC at beginning of life (BOL) – Category 1.....	16
Table 5 – PPC at beginning of life (BOL) – Categories 2 and 3	16
Table 6 – PPC at end of life (EOL) – Categories 1, 2 and 3	17
Table 7 – PPC at end of life (EOL) – Category 1	18
Table 8 – PPC at end of life (EOL) – Categories 2 and 3	18
Table 9 – Pulse profile PP1	19
Table 10 – PPC procedure option PP2.....	20
Table 11 – Charge recovery (CR) test with continuous 72 h discharge phase	21
Table 12 – Charge recovery (CR) test with pulsed 72 h discharge phase	22
Table 13 – Endurance 50 % DoD – Cycling part.....	24
Table 14 – Optional endurance cycle test	25
Table 15 – Endurance 17,5 % DoD – Cycling units	26
Table 16 – Summary of requirements – General automotive batteries	27
Table 17 – Summary of requirements Category (CAT) 1, 2 and 3.....	28
Table 18 – PPC requirements (PP1): Beginning of life (BOL)	28
Table 19 – PPC requirements (PP1): End of life (EOL)	28
Table 20 – PPC requirements (PP2): Beginning of life (BOL)	29
Table 21 – PPC requirements (PP2): End of life (EOL)	29
Table 22 – Charge recovery requirements	29
Table A.1 – Template for result reporting	30
Table B.1 – <i>T</i> -loop pulse power mapping – SOC sequence	42
Table B.2 – <i>T</i> -loop pulse power mapping – Temperature loop sequence	43
Table B.3 – <i>T</i> -loop pulse power mapping – PP5 pulse sequence.....	44
Table B.4 – SOC-loop pulse power characterization – SOC sequence at one temperature	45
Table B.5 – Pulse power characterization – PP2 pulse sequence.....	46

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**Lead-acid starter batteries -
Part 8: 12 V Batteries used in automobiles
for auxiliary or backup purposes**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 60095-8 has been prepared by IEC technical committee 21: Secondary cells and batteries. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
21/1307/FDIS	21/1321/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all the parts in the IEC 60095 series, published under the general title *Lead-acid starter batteries*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INTRODUCTION

With the growth of electrified vehicles (xEV), many 12 V batteries in automobiles are not (or not regularly) used for cranking or starting engines: In battery-electric vehicles, there is no engine. In hybrid-electric vehicles, depending on powertrain topology, the electric machine can start the combustion engine utilizing power by the traction battery. Additional functionalities like the ones related to functional safety (e.g. in case of disruption of 12 V supply from the main high voltage energy system) require new test methods, particularly for power capability and charge recovery, as well as potential different ageing mechanisms related to different usage profiles. For example, the 12 V system is operated for significantly more hours per month than in a conventional car with internal combustion engine under the same driving usage, adding the on-plug time during which the traction battery is recharged, and potentially kept at standby for grid-connected storage functions.

Current production vehicles, including some internal combustion engine (ICE) start-stop vehicles, but mainly xEVs, such as hybrid electric vehicles (HEVs), plug-in hybrid electric vehicles (PHEVs) and battery electric vehicles (BEVs), already feature one or more 12 V support batteries and are expected to be equipped with such batteries as long as a 12 V power supply system forms part of the vehicle electrical system.

1 Scope

This part of IEC 60095 is applicable to lead acid batteries with a nominal voltage of 12 V, for automobile passenger cars applications, used as auxiliary energy storage and power source in vehicles, but not featuring the classical function of engine starting or cranking. This includes applications in battery-electric vehicles, as well as in vehicles with an internal combustion engine (ICE) that is started by another (12 V, 48 V or high-volt) battery. This document can be used for batteries with auxiliary or backup purposes.

This document specifies:

- the general requirements; and
- the essential functional characteristics, relevant test methods and results required for several classes of batteries in accordance with:
 - the general type of application;
 - the type of product; and
 - the categories as defined in 4.1.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-482, *International Electrotechnical Vocabulary (IEV) - Part 482: Primary and secondary cells and batteries*

IEC 60095-1:2018, *Lead-acid starter batteries - Part 1: General requirements and methods of test*

IEC 60095-2, *Lead-acid starter batteries - Part 2: Dimensions of batteries and dimensions and marking of terminals*

IEC 60095-6:2019, *Lead-acid starter batteries - Part 6: Batteries for micro-cycle applications*