

# INTERNATIONAL STANDARD

# IEC 61169-16

QC 222400

First edition  
2006-12

---

---

## Radio-frequency connectors –

### Part 16:

### Sectional specification –

### RF coaxial connectors with inner diameter of outer conductor 7 mm (0,276 in) with screw coupling – Characteristics impedance 50 $\Omega$ (75 $\Omega$ ) (type N)

© IEC 2006 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland  
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: [inmail@iec.ch](mailto:inmail@iec.ch) Web: [www.iec.ch](http://www.iec.ch)



Commission Electrotechnique Internationale  
International Electrotechnical Commission  
Международная Электротехническая Комиссия

PRICE CODE

V

*For price, see current catalogue*

## CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references .....	6
3 IEC type designation .....	7
4 Interface dimensions .....	7
4.1 Dimensions – General purpose connectors – Grade 2 .....	7
5 Mechanical gauges and standard test connectors.....	12
5.1 Mechanical gauges.....	12
5.2 Standard test connectors – Grade 0 .....	13
6 Overall dimensions .....	17
7 Quality assessment procedures .....	17
7.1 General.....	17
7.2 Ratings and characteristics .....	17
7.3 Test schedule and inspection requirements .....	20
7.4 Procedures.....	22
8 Instructions for preparation of detail specifications .....	22
8.1 General.....	22
8.2 Identification of the Detail specification .....	22
8.3 Identification of the component.....	23
8.4 Performance.....	23
8.5 Marking, ordering information and related matters .....	23
8.6 Selection of tests, test conditions and severities.....	23
8.7 Blank detail specification pro-forma for type N connector .....	24
 Annex A (informative) Guidance information for interface dimensions of 75 Ω characteristic impedance general purpose connectors .....	 29
 Figure 1 – Connector with pin centre contact .....	 8
Figure 2 – Details of pin centre contact .....	8
Figure 3 – Connector with socket centre contact .....	10
Figure 4 – Details of socket centre contact .....	10
Figure 5 – Gauge rings for outer contact of pin connector .....	12
Figure 6 – Gauge and test pins for socket centre contact .....	13
Figure 7 – Standard test connector with pin centre contact .....	14
Figure 8 – Details of pin centre contact .....	14
Figure 9 – Standard test connector with socket centre contact .....	16
Figure 10 – Details of socket centre contact .....	16
Figure A.1 – Details of pin centre contact.....	29
 Table 1 – Dimensions for connector with pin centre contact.....	 9
Table 2 – Dimensions for connector with socket centre contact.....	11
Table 3 – Dimensions for test pins for socket centre contact.....	13
Table 4 – Dimensions for standard test connector with pin centre contact.....	15

Table 5 – Dimensions for standard test connector with socket centre contact .....	17
Table 6 – Ratings and characteristics .....	18
Table 7 – Acceptance tests .....	20
Table 8 – Periodic tests .....	21

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**RADIO-FREQUENCY CONNECTORS –****Part 16: Sectional specification – RF coaxial connectors with inner diameter of outer conductor 7 mm (0,276 in) with screw coupling – Characteristics impedance 50  $\Omega$  (75  $\Omega$ ) (type N)**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61169-16 has been prepared by subcommittee 46F: R.F. and microwave passive components, of IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

This part of IEC 61169 cancels and replaces IEC 60169-16 published in 1982 and Amendment 1 (1996). This edition constitutes a technical revision.

This edition included the following significant technical changes with respect to IEC 60169-16:

Clauses 7 and 8 have been totally re-written and Clause 9 has been removed. Clause 7 currently includes test schedules and Clause 8 gives indications to fill a Blank Detail Specification (BDS).

The text of this standard is based on the following documents:

FDIS	Report on voting
46F/54/FDIS	46F/59/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

The QC numbers that appear on the front cover of this publication are the specification numbers in the IEC Quality Assessment System for Electronic Components (IECQ).

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61169 series, under the general title *Radio frequency connectors*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

## RADIO-FREQUENCY CONNECTORS –

### **Part 16: Sectional specification – RF coaxial connectors with inner diameter of outer conductor 7 mm (0,276 in) with screw coupling – Characteristics impedance 50 $\Omega$ (75 $\Omega$ ) (type N)**

#### **1 Scope**

This part of IEC 61169, which is a Sectional Specification (SS), provides information and rules for the preparation of Detail Specifications (DS) for pin and socket R.F. coaxial connectors, with screw coupling mechanism, for low to medium power applications. The connector is commonly known as the "type N".

Three versions of the 50  $\Omega$  characteristic impedance type N connector are included, each version being mateable with each of the others.

The general purpose connector (grade 2) derived from the specifications MIL-C17B and MIL-C-39012 may preferably be used with R.F. cable 60096 IEC 50-7 up to about 12 GHz maximum frequency.

The high performance connector (grade 1) is particularly suitable for microwave applications when lower reflection factors than are offered by the general purpose connector are required. The connectors may also be suitable for microwave components. The tolerances of the interface dimensions lie between those for grade 0 and grade 2, and are chosen to give the performance required. Some grade 1 connectors conforming to this specification may be used up to 18 GHz maximum frequency.

The standard test connector (grade 0) has a closely controlled interface to provide a reference for the measurement of connectors, cable assemblies, components and equipment with the above two interfaces. It may also be used as a microwave connector in situations when the most precise interface for use up to 18 GHz maximum frequency is required.

A 75  $\Omega$  characteristic impedance connector is given in Annex A even though the use of 75  $\Omega$  type N connectors is strongly deprecated.

Accidental cross-coupling of 75  $\Omega$  with 50  $\Omega$  connectors can destructively damage the 75  $\Omega$  version, but in view of the extensive use of a number of marginally different 75  $\Omega$  versions, the interface now given provides common design guidance. 75  $\Omega$  connectors should be clearly identified.

This specification indicates the recommended performance characteristics to be considered when writing a DS and covers test schedules and inspection requirements.

#### **2 Normative references**

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-1:1988, *Environmental testing – Part 1: General and guidance*  
Amendment 1 (1992)

IEC 60096-2:1988, *Radio-frequency cables – Part 2: Relevant cable specifications*

IEC 61169-1:1992, *Radio-frequency connectors – Part 1: Generic specification – General requirements and measuring methods*

Amendment 1 (1996)

Amendment 2 (1997)

ISO 263:1973, *ISO inch screw threads – General plan and selection for screws, bolts and nuts – Diameter range 0.06 to 6 in*